

SAFETY DATA SHEET

Blasocut Eltec 200 HDD

Section 1. Identification of the substance/mixture and of the company/undertaking

GHS product identifier : Blasocut Eltec 200 HDD

Product code : 07200-02

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use only. Metal working fluids
Uses advised against
Consumer use.

Manufacturer : BLASER SWISSLUBE AG
Winterseistrasse 22
CH-3415 Hasle-Rüegsau
Switzerland
Tel: +41 (0)34 460 01 01
E-Mail: contact@blaser.com

Supplier's details : Best Lube Co. Ltd.
69 Soi Ratchadapisek 36, Ratchadapisek Road, Chankasem, Jatujak
10900 Bangkok
Thailand
Tel: +66 2 939 10178
E-Mail: ch.nattavadee@bestlube.co.th

e-mail address of person responsible for this SDS : reach@blaser.com

Emergency telephone number (with hours of operation) : 001 800 120 666 751 (7 วัน/24 ชม)

Section 2. Hazards identification

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 5
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H303 - May be harmful if swallowed.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.
 P273 - Avoid release to the environment.
 P264 - Wash thoroughly after handling.
- Response** : P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
 P302 + P352 - IF ON SKIN: Wash with plenty of water.
 P332 + P313 - If skin irritation occurs: Get medical advice or attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated middle	≥10 - ≤25	CAS: 64742-46-7
Fatty acids, castor-oil, polymd.	≤9	CAS: 68604-47-7
2,2'-(cyclohexylimino)bisethanol	≤8	CAS: 4500-29-2
Alcohols, C16-18, ethoxylated propoxylated	≤6.5	CAS: 68002-96-0
1-phenoxypropan-2-ol	≤4	CAS: 770-35-4
3,5,5-trimethylhexanoic acid	≤2.5	CAS: 3302-10-1
dicyclohexylamine	≤2	CAS: 101-83-7
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	≤3	CAS: 110-25-8
6,6',6''-(1,3,5-triazine-2,4,6-triyltriimino)trihexanoic acid	≤2	CAS: 80584-91-4
2-n-butyl-benzo[d]isothiazol-3-one	<0.1	CAS: 4299-07-4

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Check for and remove any contact lenses. Get medical attention.
- Inhalation** : Avoid breathing vapor or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be harmful if swallowed.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm

Section 8. Exposure controls/personal protection

(minimum) .

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
- Respiratory protection** : A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Yellow.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : 7.8 to 8.8 [Conc. (% w/w): 5%]
- Melting point/freezing point** : Not available.
- Pour point** : <0°C (<32°F)
- Boiling point or initial boiling point and boiling range** : Not available.
- Flash point** : Open cup: Not applicable.
- Burning rate** : Not applicable.
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Not available.
- Vapor pressure** : Not available.
- Relative vapor density** : Not available.
- Relative density** : Not available.
- Density** : 0.92 g/cm³ [20°C (68°F)]
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): 28 mm²/s (28 cSt)
- Particle characteristics**
- Median particle size** : Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Shelf life: 24 months.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
Distillates (petroleum), hydrotreated middle	Rat - Oral - LD50 >5000 mg/kg
-	Rabbit - Dermal - LD50 >3160 mg/kg
Fatty acids, castor-oil, polymd.	Rat - Oral - LD50 >2000 mg/kg
2,2'-(cyclohexylimino)bisethanol	Rat - Oral - LD50 >2000 mg/kg
Alcohols, C16-18, ethoxylated propoxylated	Rat - Oral - LD50 >2000 mg/kg
1-phenoxypropan-2-ol	Rat - Oral - LD50 2830 mg/kg
-	Rat - Dermal - LD50 >2000 mg/kg
-	Rat - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours]
3,5,5-trimethylhexanoic acid	Rat - Oral - LD50 1160 mg/kg
dicyclohexylamine	Rat - Oral - LD50 373 mg/kg
-	Rabbit - Dermal - LD50 200 to 316 mg/kg
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	Rat - Oral - LD50 >5000 mg/kg
6,6',6''-(1,3,5-triazine-2,4,6-triyltriimino) trihexanoic acid	Rat - Oral - LD50 >5000 mg/kg
-	Rat - Dermal - LD50 >2000 mg/kg
2-n-butyl-benzo[d]isothiazol-3-one	Rat - Dermal - LD50 >2000 mg/kg

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Product/ingredient name	Result
-------------------------	--------

Section 11. Toxicological information

dicyclohexylamine

Rabbit - Skin - Severe irritantDuration of treatment/exposure: 24 hoursAmount/concentration applied: 2 mg

Conclusion/Summary [Product] : pH value - Used for classification

Serious eye damage/eye irritation

Product/ingredient name

dicyclohexylamine

Result**Rabbit - Eyes - Severe irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 750 ug

Conclusion/Summary [Product] : pH value - Used for classification

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name**Result**

Section 11. Toxicological information

2,2'-(cyclohexylimino)bisethanol

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (gastrointestinal tract) - Category 2

Aspiration hazard

Product/ingredient name

Distillates (petroleum), hydrotreated middle

Result

ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Blasocut Eltec 200 HDD	2529.5	>5000	N/A	N/A	77.2
Fatty acids, castor-oil, polymd.	2500	N/A	N/A	N/A	N/A
2,2'-(cyclohexylimino)bisethanol	500	N/A	N/A	N/A	N/A
Alcohols, C16-18, ethoxylated propoxylated	2500	N/A	N/A	N/A	N/A
1-phenoxypropan-2-ol	2830	2500	N/A	N/A	N/A
3,5,5-trimethylhexanoic acid	1160	N/A	N/A	N/A	N/A
dicyclohexylamine	100	300	N/A	N/A	N/A
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	N/A	N/A	N/A	N/A	1.5
6,6',6''-(1,3,5-triazine-2,4,6-triyltriimino)trihexanoic acid	N/A	2500	N/A	N/A	N/A
2-n-butyl-benzo[d]isothiazol-3-one	N/A	2500	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result
2,2'-(cyclohexylimino)bisethanol	EC50 Fish >100 mg/l [96 hours]
Alcohols, C16-18, ethoxylated propoxylated	LC50 OECD 203 Fish >100 mg/l [96 hours]
1-phenoxypropan-2-ol	LC50 Daphnia 370 mg/l [48 hours]
-	EC50 Algae >100 mg/l [96 hours]
-	EC50 Fish 220 to 460 mg/l [96 hours]
3,5,5-trimethylhexanoic acid	LC50 OECD 203 Fish 123 mg/l [96 hours]
dicyclohexylamine	Acute - LC50 Fish 12 mg/l [96 hours]
-	Acute - EC50 Daphnia 8 mg/l [48 hours]
-	Acute - NOEC Daphnia 0.016 mg/l [21 days]
-	LC50 Algae 0.38 mg/l [72 hours]
-	NOEC Algae 0.013 mg/l [72 hours]
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	LC50

Section 12. Ecological information

2-n-butyl-benzo[d]isothiazol-3-one	Fish
	1 to 10 mg/l [96 hours]
-	Acute - LC50
	Fish
-	0.15 mg/l [96 hours]
	Acute - EC50
-	Daphnia
	0.093 mg/l [48 hours]
-	Acute - EC50
	Algae
-	0.45 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Product/ingredient name	Result
Distillates (petroleum), hydrotreated middle	OECD 306 74% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated middle	-	-	Readily
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	-	85%; <28 day(s)	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1-phenoxypropan-2-ol	1.41	-	Low
3,5,5-trimethylhexanoic acid	3.2	-	Low
dicyclohexylamine	2.724	-	Low
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	3.5 to 4.2	-	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	--

Section 14. Transport information

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

Harmful Chemicals List : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Thailand : ☒ Not determined.

Section 16. Other information

History

Date of printing : 2026.02.26
Date of issue/Date of revision : 2026.02.26
Date of previous issue : 2025.11.19
Version : 3.05
Prepared by : Product Stewardship Blaser Swissslube AG

Section 16. Other information

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- EC50 = Half maximal effective concentration
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LC50 = Median lethal concentration
- LD50 = Median lethal dose
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Expert judgment
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Expert judgment
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

📌 Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.