# SAFETY DATA SHEET



B-Cool MC 600

Section 1. Identifi	ication
Product identifier	: B-Cool MC 600
Article No.	: US 11600-41
Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	
Industrial use only. Metal working fluids	
Uses advised against	
Consumer use.	
Manufactured/supplied	: Blaser Swisslube Inc. 31 Hatfield Lane Goshen, NY 10924 Tel:+1 845 294 32 00 Mail: mailboxusa@blaser.com
e-mail address of person responsible for this SDS	: reach@blaser.com
Emergency telephone number (with hours of operation)	: +1 800 579 7421 (toll free)
Section 2. Hazard	lidentification
Classification of the substance or mixture	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>         F315 - Causes skin irritation.         H319 - Causes serious eye irritation.         H361 - Suspected of damaging fertility or the unborn child.         </li> </ul>
Precautionary statements	
Prevention	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> <li>P264 - Wash thoroughly after handling.</li> </ul>
Response	<ul> <li>P308 + P313 - IF exposed or concerned: Get medical advice or attention.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P332 + P313 - If skin irritation occurs: Get medical advice or attention.</li> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337 + P313 - If eye irritation persists: Get medical advice or attention.</li> </ul>





**Storage** Disposal

- : P405 Store locked up.

SLUBE

- ŝ,
  - **P**501 Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Section 3. Composition/information on ingredients

Sul	bst	an	ce/	mi	xtı	ıre
- u						

: Mixture

Ingredient name	% (w/w)	Identifiers
₱ stillates (petroleum), hydrotreated heavy naphthenic	≥10 - <30	CAS: 64742-52-5
1-aminopropan-2-ol	≥5 - <10	CAS: 78-96-6
Phosphoric acid, isotridecyl ester	≥1 - <5	CAS: 52933-07-0
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen-1-yloxy]-	≥0.1 - <1	CAS: 57635-48-0
dodecanedioic acid	≥0.1 - <1	CAS: 693-23-2

#### Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and would require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

Description of necessary first a	aid measures
Eye contact :	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation :	Kooid breathing vapor or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact :	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion :	✓ ash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/effe	cts, acute and delayed
Potential acute health effects	
· · · · · · · · · · · · · · · · · · ·	Causes serious eye irritation.
Inhalation :	No known significant effects or critical hazards.



Skin contact	:	Causes skin irritation.
Ingestion	1	No known significant effects or critical hazards.
Over-exposure signs/sympto	om	<u>15</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. **Specific treatments** : No specific treatment. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.





# Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions Methods and materials for co		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	E Vut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: (minimum) 18 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	CA Ontario Provincial (Canada, 6/2019) [Mineral oil, excluding metal working fluids (pure, highly and severely refined)] TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable particulate matter CA Alberta Provincial (Canada, 3/2023) [Oil] OEL 8 hours: 5 mg/m <sup>3</sup> . Form: Mist. OEL 15 minutes: 10 mg/m <sup>3</sup> . Form: Mist.

#### **Biological exposure indices**

No exposure indices known.

Appropriate engineering controls	:	We user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection		Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
Respiratory protection	:	A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.





# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>					
Physical state	:	Liquid.			
Color	:	Yellowish.			
Odor	:	Amine-like.			
Odor threshold	:	Not available.			
рН	:	8.8 to 9.4 [Conc. (% w/w): 5%]			
Melting point/freezing point	:	Not available.			
Boiling point or initial boiling point and boiling range	:	Not available.			
Flash point	:	Open cup: Not applicable.			
Flammability	:	Not available.			
Lower and upper explosion limit/flammability limit	1	Not available.			
Vapor pressure	:	Not available.			
Relative vapor density	1	: Not available.			
Relative density	:	Not available.			
Density	:	0.991 g/cm³ [20°C (68°F)]			
Solubility in water	1	Not available.			
Dispersibility	1				
Media		Result			
cold water hot water		Dispersible Dispersible			
Partition coefficient: n- octanol/water	1	Not applicable.			
Auto-ignition temperature	:	Not available.			
Decomposition temperature	:	Not available.			
Viscosity	:	Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): 40.1 mm²/s (40.1 cSt)			

Particle characteristics Median particle size

: Not applicable.

# Section 10. Stability and reactivityReactivity: No specific test data related to reactivity available for this product or its ingredients.Chemical stability: Shelf life: (minimum) 18 months.Possibility of hazardous<br/>reactions: Under normal conditions of storage and use, hazardous reactions will not occur.Conditions to avoid: No specific data.Incompatible materials: No specific data.



# Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Dermal	Rabbit	>5000 mg/kg	-
·	LD50 Oral	Rat	>5000 mg/kg	-
1-aminopropan-2-ol	LD50 Dermal	Rabbit	1851 mg/kg	-
	LD50 Oral	Rat	2098 mg/kg	-
Phosphoric acid, isotridecyl ester	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Poly(oxy-1,2-ethanediyl), α- (carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	LD50 Oral	Rat	>2000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-aminopropan-2-ol	Eyes - Severe irritant	Rabbit	-	24 hours 250 ug	-
	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	970 ug 24 hours 500	-
	Skin - Moderate irritant	Rabbit	-	mg 485 mg	-

#### **Conclusion/Summary**

Skin

: Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4. pH value - Used for classification

Eyes

: Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4. pH value - Used for classification

#### **Respiratory or skin sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
<b>∦-</b> aminopropan-2-ol	-	Equivocal		unspecified	Route of exposure unreported	-

#### **Teratogenicity**

Not available.

#### <u>Specific target organ toxicity (single exposure)</u>

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.



# Section 11. Toxicological information

Aspiration hazard				
Product/ingredient name		Result		
Distillates (petroleum), hyd	ASPIRATION HAZARD - Category 1			
Information on the likely routes of exposure	: Not available.			
Potential acute health effec	<u>:ts</u>			
Eye contact	: Causes serious eye irr	ritation.		
Inhalation	: No known significant e	effects or critical hazards.		
Skin contact	: Causes skin irritation.			
Ingestion	: No known significant e	effects or critical hazards.		
Symptoms related to the pl	nysical, chemical and toxic	cological characteristics		
Eye contact	: Adverse symptoms ma pain or irritation watering redness	ay include the following:		
Inhalation	: Adverse symptoms ma reduced fetal weight increase in fetal deaths skeletal malformations			
Skin contact	: Adverse symptoms ma irritation redness reduced fetal weight increase in fetal deaths skeletal malformations			
Ingestion	: Adverse symptoms ma reduced fetal weight increase in fetal deaths skeletal malformations			
Delayed and immediate effo	ects and also chronic effec	cts from short and long term exposure		
Short term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	Not available.			
Long term exposure				
Potential immediate effects	: Not available.	: Not available.		
Potential delayed effects	Not available.			
Potential chronic health e Not available.	ffects			
General	• No known significant e	effects or critical hazards.		
Carcinogenicity	-			
Carcinogenicity	: No known significant effects or critical hazards.			

- **Mutagenicity** : No known significant effects or critical hazards.
- **Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

Numerical r	<u>neasures</u>	of toxicity
Acute toxi	<u>city estim</u>	<u>nates</u>



Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
B-Cool MC 600	>2000	>2000	N/A	N/A	N/A
1-aminopropan-2-ol	2098	1851	N/A	N/A	N/A
Phosphoric acid, isotridecyl ester	2500	2500	N/A	N/A	N/A
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	2500	N/A	N/A	N/A	N/A

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	EC50 >1000 mg/l	Fish	96 hours
Conclusion/Summary	: On basis of test data		

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1-aminopropan-2-ol		0.11	Low
dodecanedioic acid	3.2	3.162	Low

#### Mobility in soil

Soil/water partition : coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SSLUBE



# Section 14. Transport information

	TDG Classification	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

#### Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

# Section 15. Regulatory information

#### **Canadian lists**

**Canadian NPRI** 

- : None of the components are listed.
- **CEPA Toxic substances**
- : None of the components are listed.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Canada

: At least one component is not listed.

: 3. Dec 2024 Date of previous issue

**United States** 

Date of issue/Date of revision

: All components are active or exempted.

# Section 16. Other information

#### IP346:

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

<u>History</u>	
Date of printing	: 3. Dec 2024

: 15. Jul 2024

10/11 CA

Version 1.09:



# Section 16. Other information

Date of issue/Date of revision	: 3. Dec 2024
Date of previous issue	: 15. Jul 2024
Version	: 1.09
Prepared by	: Product Stewardship Blaser Swisslube AG
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
KIN IRRITATION - Category 2	Expert judgment
EYE IRRITATION - Category 2A	Expert judgment
TOXIC TO REPRODUCTION - Category 2	Calculation method

: Not available. References

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.