# SAFETY DATA SHEET

### according to Hazardous Products Regulations (HPR)



Blasocut BC 20 SW

# **Section 1. Identification**

**Product identifier** : Blasocut BC 20 SW

: US 01200-69 Article No.

# Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Metal working fluids Industrial use only.

**Uses advised against** 

Consumer use.

Manufactured/supplied : Blaser Swisslube Inc.

> 31 Hatfield Lane Goshen, NY 10924 Tel:+1 845 294 32 00

Mail: mailboxusa@blaser.com

e-mail address of person

responsible for this SDS

: reach@blaser.com

**Emergency telephone** number (with hours of

operation)

: +1 800 579 7421 (toll free)

# Section 2. Hazard identification

Classification of the substance or mixture : EYE IRRITATION - Category 2A

### **GHS** label elements

**Hazard pictograms** 



Signal word : Warning

**Hazard statements** : H319 - Causes serious eye irritation.

**Precautionary statements** 

**Prevention** : P280 - Wear eye or face protection.

P264 - Wash thoroughly after handling.

: P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

: Not applicable. **Storage Disposal** : Not applicable.

Date of issue/Date of revision : 27. Apr 2024 : 4. Sep 2024 Date of previous issue Version 1.05: 1/11 CA



# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers
vistillates (petroleum), hydrotreated heavy naphthenic	≥30 - <60	CAS: 64742-52-5
2,2'-(methylimino)diethanol	≥5 - <10	CAS: 105-59-9
1-phenoxypropan-2-ol	≥5 - <10	CAS: 770-35-4
Natrium-Petrolsulfonat (60%)	≥5 - <10	CAS: 68608-26-4
2-dibutylaminoethanol	≥1 - <5	CAS: 102-81-8
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen-1-yloxy]-	≥1 - <5	CAS: 57635-48-0
2-phenylphenol (ISO)	≥1 - <5	CAS: 90-43-7

#### Additional information:

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and would require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Avoid breathing vapor or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

Date of issue/Date of revision : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05: 2/11 CA



# Section 4. First-aid measures

: No known significant effects or critical hazards. Skin contact Ingestion : No known significant effects or critical hazards.

**Over-exposure signs/symptoms** 

: Adverse symptoms may include the following: **Eye contact** 

redness

pain or irritation watering

Inhalation : No specific data. Skin contact : No specific data. : No specific data. Ingestion

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides carbonyl halides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision : 27. Apr 2024 Version 1.05: 3/11 CA : 4. Sep 2024 Date of previous issue



# Section 6. Accidental release measures

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### **Advice on general** occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: -70 to 40°C (-94 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

# **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
vistillates (petroleum), hydrotreated heavy naphthenic	CA Ontario Provincial (Canada, 6/2019) [Mineral oil, excluding metal working fluids (pure, highly and severely refined)] TWA 8 hours: 5 mg/m³. Form: Inhalable particulate matter CA Alberta Provincial (Canada, 3/2023) [Oil] OEL 8 hours: 5 mg/m³. Form: Mist. OEL 15 minutes: 10 mg/m³. Form: Mist.

### **Biological exposure indices**

No exposure indices known.



# Section 8. Exposure controls/personal protection

Appropriate engineering controls

**Environmental exposure** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.

**Respiratory protection** 

: A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.
Color : Brown.
Odor : Agreeable.
Odor threshold : Not available.

**pH** : 8.6 to 9.5 [Conc. (% w/w): 5%]

Melting point/freezing point : Not available.

Pour point : <-30°C (<-22°F)

Boiling point or initial : Not available.

range

boiling point and boiling

Flash point : Open cup: >148°C (>298.4°F)

Flammability : Not available.

Date of issue/Date of revision : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05: 5/11 CA



# Section 9. Physical and chemical properties and safety characteristics

Lower and upper explosion limit/flammability limit

Not available.

Vapor pressure **Relative vapor density** 

: Not available. : Not available. Not available.

**Relative density Density** 

: 0.963 g/cm3 [20°C (68°F)]

Solubility in water

Not available.

**Dispersibility** 

Media	Result
cold water hot water	Dispersible Dispersible

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature Decomposition temperature**  : Not available.

: Not available.

**Viscosity** 

: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): 62 mm<sup>2</sup>/s (62 cSt)

**Particle characteristics** 

Median particle size

: Not applicable.

# Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: Shelf life: 24 months.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: No specific data.

Incompatible materials

: No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	<b>Exposure</b>
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Dermal	Rabbit	>5000 mg/kg	-
·	LD50 Oral	Rat	>5000 mg/kg	_
2,2'-(methylimino)diethanol	LD50 Dermal	Rabbit	>2000 mg/kg	_
,	LD50 Oral	Rat	4680 mg/kg	-
1-phenoxypropan-2-ol	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-dibutylaminoethanol	LD50 Dermal	Rabbit	1680 mg/kg	_

Date of issue/Date of revision : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05: 6/11



# Section 11. Toxicological information

LD50 Oral	Rat	1070 mg/kg	-
LD50 Oral	Rat	>2000 mg/kg	-
LD50 Dermal	Rat - Male,	>5000 mg/kg	-
	Female		
LD50 Oral	Rat - Male,	2733 mg/kg	-
	Female		
	LD50 Oral  LD50 Dermal	LD50 Oral  Rat  LD50 Dermal  Rat - Male, Female  LD50 Oral  Rat - Male,	LD50 Oral       Rat       >2000 mg/kg         LD50 Dermal       Rat - Male, Female       >5000 mg/kg         LD50 Oral       Rat - Male, Rat - Male, 2733 mg/kg

# **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-dibutylaminoethanol	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-
2-phenylphenol (ISO)	Skin - Severe irritant Eyes - Severe irritant	Rabbit Rabbit	-	500 mg 24 hours 50	-
	Skin - Mild irritant	Human	-	ug 76 hours 0.5 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-

### **Conclusion/Summary**

Skin : pH value - Used for classification

Eyes : pH value - Used for classification

### **Respiratory or skin sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

# Specific target organ toxicity (single exposure)

Product/ingredient name	3 3 3	Route of exposure	Target organs
2-dibutylaminoethanol	Category 3	-	Respiratory tract irritation
2-phenylphenol (ISO)	Category 3	-	Respiratory tract irritation

# Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy naphthenic	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Date of issue/Date of revision : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05: 7/11 CA



# **Section 11. Toxicological information**

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

# Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Blasocut BC 20 SW	>2000	>2000	N/A	N/A	N/A
2,2'-(methylimino)diethanol	4680	2500	N/A	N/A	N/A
1-phenoxypropan-2-ol	2500	2500	N/A	N/A	N/A
2-dibutylaminoethanol	1070	1680	N/A	N/A	N/A
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	2500	N/A	N/A	N/A	N/A
2-phenylphenol (ISO)	2733	N/A	N/A	N/A	N/A



# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	EC50 >1000 mg/l	Fish	96 hours
2,2'-(methylimino)diethanol	EC50 >100 mg/l	Algae	72 hours
	EC50 233 mg/l	Daphnia	48 hours
	LC50 1466 mg/l	Fish - Golden orfe	96 hours
2-dibutylaminoethanol	Acute EC10 6.9 mg/l	Aquatic plants	72 hours
	Acute EC50 21 mg/l	Aquatic plants	72 hours
	Acute EC50 73.7 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 29 mg/l	Fish	96 hours
	Chronic NOEC 4.4 mg/l	Daphnia	21 days
2-phenylphenol (ISO)	EC50 3.57 mg/l Fresh water	Algae	72 hours
	EC50 2.7 mg/l Fresh water	Daphnia	48 hours
	LC50 4.5 mg/l Fresh water	Fish	96 hours
	NOEC 0.468 mg/l Fresh water	Algae	72 hours
	Chronic NOEC 0.009 mg/l Fresh water	Daphnia	21 days

### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-(methylimino)diethanol 2-phenylphenol (ISO)		96%; < 28 day(s) 70.8 to 75.7%; 28 day(s)	-

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2,2'-(methylimino)diethanol	-1.08	0.7 to 3.2	Low
1-phenoxypropan-2-ol	1.41	-	Low
2-dibutylaminoethanol	-	<39	Low
2-phenylphenol (ISO)	3.18	22	Low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

# **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05: 9/11 CA



# **Section 14. Transport information**

	TDG Classification	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

# Section 15. Regulatory information

#### **Canadian lists**

**Canadian NPRI** : None of the components are listed.

**CEPA Toxic substances** : The following components are listed: chlorinated alkanes

**International regulations** 

### Chemical Weapon Convention List Schedules I, II & III Chemicals

List name	Ingredient name	Status
Schedule III	Methyldiethanolamine	Listed

### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Canada : All components are listed or exempted. **United States** : All components are active or exempted.

Date of issue/Date of revision 10/11 CA : 4. Sep 2024 Date of previous issue : 27. Apr 2024 Version 1.05:



# Section 16. Other information

#### **IP346**:

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

#### **History**

Date of printing : 4. Sep 2024

Date of issue/Date of : 4. Sep 2024

revision

Date of previous issue : 27. Apr 2024

Version : 1.05

Prepared by : Product Stewardship Blaser Swisslube AG

**Key to abbreviations** : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HPR = Hazardous Products Regulations IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
EYE IRRITATION - Category 2A	Expert judgment

References : Not available.

✓ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.