

Reviewed on 07/31/2020

Issued on 07/31/2020

Edition number 1

1 Identification

Product identifier

Trade name: Additive M62

Article number: 03147-01 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the preparation: For industrial use only Metal working auxiliary Additive

Details of the supplier of the safety data sheet Manufacturer / Supplier:

BLASER SWISSLUBE, Inc. 31 Hatfield Lane Goshen, NY 10924 USA Phone: +1 (0) 845 294 32 00 Fax .: +1 (0) 845 294 31 02 Mailto: mailboxusa@blaser.com

Information department:

Product Safety Department E-mail: sds@blaser.com

Emergency telephone number:

For advice on chemical emergencies, spillages, fires or exposures: +1 866 928 0789 (Toll free).

2 Hazard(s) identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Classification of the substance or mixture

Causes skin irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

Label elements

GHS label elements The product is classified and labeled according to 29 CFR 1910.1200 (OSHA Hazcom 2012). **Hazard pictograms**



Signal word Danger

Hazard-determining components of labeling: Paraffin based neutral lubricating oil, hydrotreated, C₁₅-C₃₀ 1H-benzotriazole-1-methanamine,N,N-bis(2-ethylhexyl)-ar-methyl-Hazard statements H315 Causes skin irritation. H317 May cause an allergic skin reaction. H304 May be fatal if swallowed and enters airways. Precautionary statements P280 Wear protective gloves. P301+P310 If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. P331 P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Edition number 1



Reviewed on 07/31/2020

Issued on 07/31/2020 Trade name: Additive M62

Other hazards None

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description:

Mixture of the substances listed below with nonhazardous additions. Solvent mixture with additives

Declarable components:

CAS no.

72623-86-0 Paraffin based neutral lubricating oil, hydrotreated, C_{15} - C_{30}	>50-<80%
94270-86-7 1H-benzotriazole-1-methanamine,N,N-bis(2-ethylhexyl)-ar-methyl-	>20-<30%

Additional information:

The specific chemical identity and/or exact percentage concentration of proprietary components is withheld as a trade secret.

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Not applicable, as the concentrate is not volatile.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; immediately call for medical help.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available. **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray. **For safety reasons unsuitable extinguishing agents:** Water with full jet

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Edition number 1



Reviewed on 07/31/2020

Issued on 07/31/2020 Trade name: Additive M62

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

The product has been classified and marked in accordance with directives on hazardous materials. Observe the general safety regulations when handling chemicals.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle. **Information about storage in one common storage facility:**

Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Optimal storage temperature between 32°F and 104°F

Minimum shelf life: In closed, original container, at least 24 months.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values at the workplace:

72623-86-0 Paraffin based neutral lubricating oil, hydrotreated, C₁₅-C₃₀

ACGIH TLV (US) Long-term value: 5 mg/m³ OSHA PEL (US) Long-term value: 5 mg/m³

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin. Respiratory Protection: Not required. Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves (recommended):** Suitable protective gloves: Nitrile gloves, minimum thickness of 0.3 mm. **Breakthrough time of glove material:**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. **Eye protection (recommended):**

Eye protector with side protection (framed eyeglasses) ANSI Z87.1 – 2010

Edition number 1



Reviewed on 07/31/2020

Issued on 07/31/2020

Trade name: Additive M62

Use of tight fitting goggles Body protection (recommended): Protective work clothing

Color:LigOdor:ChOdor threshold:NopH-value:NopH-value:NoChange in condition:UrMelting point/Melting range:UrBoiling point/Boiling range:>2Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoOxidizing propertiesNoRelative density0.8	quid ght yellow haracteristic ot determined. ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific ot determined.
Form:LiaColor:LiaOdor:ChOdor threshold:NapH-value:NaChange in condition:Melting point/Melting range:Melting point/Melting range:UrBoiling point/Boiling range:>2Flash point:>1Evaporation rateNaFlammability (solid, gaseous):NaExplosion limits (@1013 mbar):geLower:NaOxidizing propertiesNaRelative density0.8	ght yellow haracteristic ot determined. ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Form:LiaColor:LiaOdor:ChOdor threshold:NapH-value:NaChange in condition:Melting point/Melting range:Melting point/Melting range:UrBoiling point/Boiling range:>2Flash point:>1Evaporation rateNaFlammability (solid, gaseous):NaExplosion limits (@1013 mbar):geLower:NaOxidizing propertiesNaRelative density0.8	ght yellow haracteristic ot determined. ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Odor:ChOdor threshold:NopH-value:NopH-value:NoChange in condition:Melting point/Melting range:Melting point/Melting range:VrBoiling point/Boiling range:>2Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoOxidizing propertiesNoRelative density0.8	haracteristic ot determined. ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Odor threshold:NopH-value:NoChange in condition: Melting point/Melting range:UrBoiling point/Boiling range:>2Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoOxidizing propertiesNoRelative density0.8	ot determined. ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
pH-value: No Change in condition: Melting point/Melting range: Ur Boiling point/Boiling range: >2 Flash point: >1 Evaporation rate No Flammability (solid, gaseous): No Explosion limits (@1013 mbar): get Lower: No Oxidizing properties No Relative density 0.8	ot applicable. ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Change in condition: Melting point/Melting range: Ur Boiling point/Boiling range: >2 Flash point: >1 Evaporation rate No Flammability (solid, gaseous): No Explosion limits (@1013 mbar): ge Lower: No Oxidizing properties No Relative density 0.8	ndetermined. 250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Melting point/Melting range:Ur Boiling point/Boiling range:>2Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.5	250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Boiling point/Boiling range:>2Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.8	250 °C (>482 °F) (DIN 51751 / ASTM D86) 150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Flash point:>1Evaporation rateNoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.5	150 °C (>302 °F) (ISO 2592 / ASTM D92) ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Evaporation rateNoFlammability (solid, gaseous):NoFlammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.5	ot determined. ot applicable. eneral values for mineral oil, therefore not product specific
Flammability (solid, gaseous):NoExplosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.8	ot applicable. eneral values for mineral oil, therefore not product specific
Explosion limits (@1013 mbar):geLower:NoUpper:NoOxidizing propertiesNoRelative density0.8	eneral values for mineral oil, therefore not product specific
Lower:NoUpper:NoOxidizing propertiesNoRelative density0.8	
Upper:NoOxidizing propertiesNoRelative density0.8	at determined
Oxidizing propertiesNoRelative density0.8	or determined.
Relative density 0.8	ot determined.
-	ot applicable.
	85 @ 68°F (20°C) (DIN 51757 / ASTM D1217)
	ot applicable.
	ot determined.
Evaporation rate No	ot determined.
Solubility in / Miscibility with	
Water: Ins	soluble.
Partition coefficient (n-octanol/water): No	
	roduct is not selfigniting.
Decomposition temperature: No	ot determined.
Viscosity	
Kinematic at 40 °C (104 °F): 12	2 mm²/s (ISO 3104 / ASTM D445)
VOC content: No	ot determined.
Other information: no	one

10 Stability and reactivity

Reactivity None known if used as directed.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

(Contd. on page 5)

(Contd. of page 3)

Edition number 1

Blaser. SWISSLUBE

Reviewed on 07/31/2020

Issued on 07/31/2020

Trade name: Additive M62

Hazardous decomposition products (in case of fire or oxidation): Carbon monoxide and carbon dioxide

11 Toxicological information

Information on toxicological effects Acute toxicity:

LD/LC50 values that are relevant for classification:

106-20-7 bis(2-ethylhexyl)amine

Oral LD50 1,640 mg/kg (rat) Dermal LD50 1,190 mg/kg (rabbit)

Primary irritant effect:

on the skin: Causes skin irritation.

on the eye: No irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

IARC (International Agency for Research on Cancer)

None of the ingredients is listed in groups 1, 2A, or 2B.

NTP (National Toxicology Program)

None of the ingredients are listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Behavior in environmental systems: Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available. Additional ecological information: General notes: Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Used containers

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

USA

(Contd. of page 4)

Edition number 1



Reviewed on 07/31/2020

(Contd. of page 5)

Issued on 07/31/2020

Trade name: Additive M62

4 Transport information		
UN-Number DOT, IMDG, IATA DOT, IMDG, IATA	Not regulated Not regulated	
DOT, IMDG, IATA Hazard Classification: DOT, IMDG, IATA	Not regulated Not regulated	
Environmental hazards	Not applicable.	
Special precautions for user	Not applicable.	
Transport/Additional information: Not hazardous according to the above specifications.		
ΙΑΤΑ	IATA Dangerous Goods Regulation (DGR): latest edition	
UN "Model Regulation":	Not regulated	

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

SARA (Superfund Amendments and Reauthorization)

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

This product does not contain a chemical that are listed in Section 313.

TSCA (Toxic Substances Control Act):

All ingredients are listed on the U.S. TSCA inventory or exempt from premanufacture notice requirements.

California Proposition 65

This product contains one or more chemicals listed under California Proposition 65. Such chemicals are not used as raw materials in the product formulation but rather are typical impurities.

Carcinogenic categories:

EPA (Environmental Protection Agency)

None of the ingredients are listed.

NIOSH-Carcinogen list

None of the ingredients are listed.

California SCAQMD Rule 1144: Not applicable. GHS label elements GHS label elements are issued under section 2.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H.R.2420 (RoHS):

This product fulfill the H.R.2420 requirements in that the EDEE Act regulated materials are absent or their concentrations are significantly below regulatory thresholds.

BSE/TSE:

Materials and/or synthetically modified materials which are of animal origin from bovine, ovine, goats, cats, dogs, deer, elk and/or mink, are NOT included in this product.

(Contd. on page 7)

Edition number 1



Reviewed on 07/31/2020

(Contd. of page 6)

Trade name: Additive M62

Issued on 07/31/2020

NFPA ratings (scale 0-4)



Health = 1 Fire = 1 Reactivity = 0

Department issuing SDS: Product Stewardship

Editor's notice:

The above mentioned data correspond to our present state of knowledge and experience. The safety data sheet serves as description of the products in regard to necessary safety measures. The indications have not the meaning of guarantees on properties.

Abbreviations and acronyms:

RoHS: Restriction of Hazardous Substances ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) ISO: International Organisation for Standardisation LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic chemicals vPvB: very Persistent and very Bioaccumulative chemicals NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration ATE: Acute Toxicity Estimate Skin Irrit. 2: Skin corrosion/irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Asp. Tox. 1: Aspiration hazard - Category 1 * Data compared to the previous version altered. The asterisk (*) on the left side indicate the respective changes from the previous version.

USA