SAFETY DATA SHEET



B-Cool 755

Section 1. Identification **GHS** product identifier : B-Cool 755 Article No. : US 11755-45 **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against **Identified uses** Industrial use only. Metal working fluids Uses advised against Consumer use. Manufactured/supplied : Blaser Swisslube Inc. 31 Hatfield Lane Goshen, NY 10924 Tel:+1 845 294 32 00 Mail: mailboxusa@blaser.com e-mail address of person : reach@blaser.com responsible for this SDS **Emergency telephone** : +1 866 928 0789 (Toll free) number (with hours of operation) Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Classification of the** : SKIN IRRITATION - Category 2 **EYE IRRITATION - Category 2A** substance or mixture **TOXIC TO REPRODUCTION - Category 2 GHS** label elements **Hazard pictograms** ÷. Signal word : Warning **Hazard statements** : H315 - Causes skin irritation. H319 - Causes serious eye irritation. H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood

- P280 Wear protective gloves, protective clothing and eye or face protection.
- P264 Wash thoroughly after handling.



Section 2. Hazards identification

Response	 F308 + P313 - IF exposed or concerned: Get medical advice or attention. P302 + P352 - IF ON SKIN: Wash with plenty of water. P332 + P313 - If skin irritation occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: 🗗 405 - Store locked up.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	Identifiers
Sistillates (petroleum), hydrotreated heavy naphthenic	≥30 - ≤50	CAS: 64742-52-5
1-aminopropan-2-ol	≤10	CAS: 78-96-6
5(or 6)-carboxy-4-hexylcyclohex-2-ene-1-octanoic acid	≤10	CAS: 53980-88-4
Phosphoric acid, isotridecyl ester	≤5	CAS: 52933-07-0
2-amino-2-ethylpropanediol	≤3	CAS: 115-70-8
2-phenylphenol (ISO)	≤3	CAS: 90-43-7
Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-	≤3	CAS: 57635-48-0
2-amino-2-methylpropanol	≤3	CAS: 124-68-5
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	≤3	CAS: 110-25-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and would require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary fir	st a	d measures
Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Avoid breathing vapor or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.



Section 4. First aid measures

Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important sympt	oms/effects, acute and delayed	
Potential acute healt	h effects	
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation.	
Ingestion	: No known significant effects or critical hazards.	
<u>Over-exposure signs</u>	/symptoms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	 Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations 	
Skin contact	 Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations 	
Ingestion	 ▲ dverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations 	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. 	
Specific treatments	: No specific treatment.	

See toxicological information (Section 11)

Protection of first-aiders

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.



Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Blaser.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wa spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



Section 7. Handling and storage

Conditions for safe storage,	: Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24
including any	months. Store in accordance with local regulations. Store in original container
incompatibilities	protected from direct sunlight in a dry, cool and well-ventilated area, away from
	incompatible materials (see Section 10) and food and drink. Store locked up. Keep
	container tightly closed and sealed until ready for use. Containers that have been
	opened must be carefully resealed and kept upright to prevent leakage. Do not store in
	unlabeled containers. Use appropriate containment to avoid environmental
	contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

NIOSH Recommended exposure limit for Metalworking fluids: 0.5 mg/m3 (particulate)

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL] TWA 10 hours: 5 mg/m ³ . Form: Mist. STEL 15 minutes: 10 mg/m ³ . Form: Mist. OSHA PEL (United States, 5/2018) [Oil mist,
	mineral] TWA 8 hours: 5 mg/m ³ .
1-aminopropan-2-ol	None.
5(or 6)-carboxy-4-hexylcyclohex-2-ene-1-octanoic acid	None.
Phosphoric acid, isotridecyl ester	None.
2-amino-2-ethylpropanediol	None.
2-phenylphenol (ISO)	None.
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen- 1-yloxy]-	None.
2-amino-2-methylpropanol	None.
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls	Wuser operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	



Section 8. Exposure controls/personal protection

-	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
Respiratory protection	 A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance		
Physical state	:	Liquid.
Color	1	Tan.
Odor	1	Amine-like.
Odor threshold	1	Not available.
рН	1	8.8 to 9.6 [Conc. (% w/w): 5%]
Melting point/freezing point	1	Not available.
Pour point	1	-5.8°F
Boiling point or initial boiling point and boiling range	:	Not available.
Flash point	:	Open cup: 255.2°F (124°C)
Flammability	:	Not available.
Lower and upper explosion limit/flammability limit	:	Not available.
Vapor pressure	1	Not available.
Relative vapor density	4	Not available.
Relative density	4	Not available.
Density	4	0.94 g/cm³ [68°F (20°C)]
Solubility(ies)	1	
Media		Result
cold water hot water		Dispersible Dispersible
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	1	Not available.
Decomposition temperature	4	Not available.
Viscosity	:	Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (104°F (40°C)): 117.7 mm²/s (117.7 cSt)
VOC content	:	121 g/l (ASTM E1868-10); Concentrate in the packaging as sold.
		18.2 g/l (ASTM E1868-10); @ Maximum concentration

Date of issue/Date of revision	: 12/3/2024	Date of previous issue	: 7/15/2024	Version	: 1.04	6/13	US
--------------------------------	-------------	------------------------	-------------	---------	--------	------	----



Section 9. Physical and chemical properties and safety characteristics

Particle characteristics Median particle size

: Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Shelf life: 24 months.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Dermal	Rabbit	>5000 mg/kg	-
•	LD50 Oral	Rat	>5000 mg/kg	-
1-aminopropan-2-ol	LD50 Dermal	Rabbit	1851 mg/kg	-
	LD50 Oral	Rat	2098 mg/kg	-
5(or 6)-carboxy- 4-hexylcyclohex-2-ene- 1-octanoic acid	LD50 Oral	Rat	6176 mg/kg	-
Phosphoric acid, isotridecyl ester	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-amino-2-ethylpropanediol	LD50 Dermal	Rat	>2000 mg/kg	-
2-phenylphenol (ISO)	LD50 Dermal	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	2733 mg/kg	-
Poly(oxy-1,2-ethanediyl), α- (carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	LD50 Oral	Rat	>2000 mg/kg	-
2-amino-2-methylpropanol (Z)-N-methyl-N-(1-oxo- 9-octadecenyl)glycine	LD50 Dermal LD50 Oral	Rabbit Rat	>2000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
√-aminopropan-2-ol	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
				ug	
	Eyes - Severe irritant	Rabbit	-	970 ug	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	485 mg	-
2-phenylphenol (ISO)	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
,				ug	
	Skin - Mild irritant	Human	-	76 hours 0.5	-
				%	
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

Blaser.

Conclusion/Summary

|--|

: pH value - Used for classification

Eyes : pH value - Used for classification

Respiratory or skin sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification IARC/OSHA/NTP

Not applicable.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
raminopropan-2-ol	-	Equivocal		Mammal - species unspecified	Route of exposure unreported	-

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name		Route of exposure	Target organs
2-phenylphenol (ISO)	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy naphthenic	ASPIRATION HAZARD - Category 1

Information on the likely : Not available. routes of exposure

Potential acute health effectsEye contact: Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Date of issue/Date of revision	: 12/3/2024	Date of previous issue	: 7/15/2024	Version : 1.04	4 8/13	US
--------------------------------	-------------	------------------------	-------------	----------------	--------	----



Skin contact	: Causes skin irritation.								
Ingestion	: No known significant effects or critical hazards.								
Symptoms related to t	Symptoms related to the physical, chemical and toxicological characteristics								
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness								
Inhalation	 Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations 								
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations								
Ingestion	 Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations 								

Blaser.

Delayed and immediate effects and also chronic effects from short and long term exposure							
Short term exposure							
Potential immediate effects	:	Not available.					
Potential delayed effects	1	Not available.					
Long term exposure							
Potential immediate effects	1	Not available.					
Potential delayed effects	:	Not available.					
Potential chronic health effe	ct	<u>s</u>					
Not available.							
General	:	No known significant effects or critical hazards.					
Carcinogenicity	:	No known significant effects or critical hazards.					
Mutagenicity		No known significant effects or critical hazards.					
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.					

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
B-Cool 755	>2000	>2000	N/A	N/A	29.2
1-aminopropan-2-ol	2098	1851	N/A	N/A	N/A
5(or 6)-carboxy-4-hexylcyclohex-2-ene-1-octanoic acid	6176	N/A	N/A	N/A	N/A
Phosphoric acid, isotridecyl ester	2500	2500	N/A	N/A	N/A
2-amino-2-ethylpropanediol	N/A	2500	N/A	N/A	N/A
2-phenylphenol (ISO)	2733	N/A	N/A	N/A	N/A
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	2500	N/A	N/A	N/A	N/A
2-amino-2-methylpropanol	N/A	2500	N/A	N/A	N/A

B-Cool 755	Blaser. SWISSLUBE					
Section 11. Toxicological information						
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	N/A	N/A	N/A	N/A	1.5	

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Sistillates (petroleum), hydrotreated heavy naphthenic	EC50 >1000 mg/l	Fish	96 hours
2-phenylphenol (ISO)	EC50 3.57 mg/l Fresh water EC50 2.7 mg/l Fresh water LC50 4.5 mg/l Fresh water NOEC 0.468 mg/l Fresh water Chronic NOEC 0.009 mg/l Fresh water	Algae Daphnia Fish Algae Daphnia	72 hours 48 hours 96 hours 72 hours 21 days
2-amino-2-methylpropanol (Z)-N-methyl-N-(1-oxo- 9-octadecenyl)glycine	LC50 193 mg/l LC50 1.1 mg/l	Daphnia Fish	48 hours 96 hours
Sociadecenyi)giycine	: On basis of test data		

Persistence and degradability

Tovicity

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-phenylphenol (ISO)	-	70.8 to 75.7%; 28 day(s)	-

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
I → aminopropan-2-ol	-0.96	0.11	Low
2-phenylphenol (ISO)	3.18	22	Low
2-amino-2-methylpropanol	-0.63	-	Low
(Z)-N-methyl-N-(1-oxo-	3.5 to 4.2	-	Low
9-octadecenyl)glycine			

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) PAIR: dodecamethylcyclohexasiloxane					
	TSCA 8(a) CDR Exempt/Partial exemption: Not determined					
TSCA 12(b) - Chemical export notification						
Not applicable.						
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed					
Clean Air Act Section 602 Class I Substances	: Not listed					
Clean Air Act Section 602 Class II Substances	: Not listed					
DEA List I Chemicals (Precursor Chemicals)	: Not listed					
DEA List II Chemicals (Essential Chemicals)	: Not listed					
SARA 302/304						
Composition/information	on ingredients					
No products were found.						
SARA 304 RQ	: Not applicable.					
<u>SARA 311/312</u>						
Classification	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2					
Composition/information	Composition/information on ingredients					



Section 15. Regulatory information

	0/	
Name	%	Classification
₱ stillates (petroleum), hydrotreated heavy naphthenic	≥30 - ≤50	ASPIRATION HAZARD - Category 1
1-aminopropan-2-ol	≤10	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 TOXIC TO REPRODUCTION - Category 2
5(or 6)-carboxy-4-hexylcyclohex-2-ene-1-octanoic acid	≤10	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
Phosphoric acid, isotridecyl ester	≤5	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
2-amino-2-ethylpropanediol	≤3	SERIOUS EYE DAMAGE - Category 1
2-phenylphenol (ISO)	≤3	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	≤3	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
2-amino-2-methylpropanol	≤3	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	≤3	ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	2-phenylphenol (ISO)	90-43-7	≤3
Supplier notification	2-phenylphenol (ISO)	90-43-7	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

▲ WARNING: This product can expose you to o-Phenylphenol, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

	No significant risk level	Maximum acceptable dosage level
o-Phenylphenol	-	-

California SCAQMD Rule 1144:

Category: Metalworking Fluid – Metal Removal – General. Recordkeeping requirement: Super Compliant. (< 50 g/L VOC @ max. use concentration)

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.



Section 15. Regulatory information

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Canada

United States

: All components are listed or exempted. : All components are active or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A	Expert judgment Expert judgment
TOXIC TO REPRODUCTION - Category 2	Calculation method

IP346:

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

History

Inotory	
Date of printing	: 12/3/2024
Date of issue/Date of revision	: 12/3/2024
Date of previous issue	: 7/15/2024
Version	: 1.04
Prepared by	: Product Stewardship Blaser Swisslube AG
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
References	: Not available.

References

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

13/13