SAFETY DATA SHEET



Blaser TP 318

Section 1. Identification

GHS product identifier : Blaser TP 318 **Article No.** : 40318-01 **Product type** : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use only. Metal working fluids

Uses advised against

Consumer use.

Manufactured/supplied : BLASER SWISSLUBE AG

> Winterseistrasse 22 CH-3415 Hasle-Rüegsau

Switzerland

Tel:+41 (0)34 460 01 01 Mail: contact@blaser.com

Blaser Swisslube Inc. 31 Hatfield Lane 10924 Goshen Tel:+1 845 294 32 00

Mail: mailboxusa@blaser.com

e-mail address of person responsible for this SDS

: reach@blaser.com

Emergency telephone number (with hours of

operation)

: +1 866 928 0789 (Toll free)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.

P264 - Wash thoroughly after handling.

Date of issue/Date of revision : 12/1/2022 Date of previous issue : No previous Version 1/12 US validation



Section 2. Hazards identification

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice or attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

: Not applicable. **Storage Disposal** : Not applicable. : None known.

Hazards not otherwise classified

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
2,2'-(methylimino)diethanol	≥10 - ≤25	105-59-9
2-dibutylaminoethanol	≤3	102-81-8
Phosphoric acid, isotridecyl ester	<3	52933-07-0
2-amino-2-methylpropanol	≤3	124-68-5
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen-1-yloxy]-	≤3	57635-48-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information:

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Avoid breathing vapor or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.



Section 4. First aid measures

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date of revision : 12/1/2022 Version 3/12 US Date of previous issue : No previous : 1 validation



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 12 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

NIOSH Recommended exposure limit for Metalworking fluids: 0.5 mg/m3 (particulate)



Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
2,2'-(methylimino)diethanol	None.
2-dibutylaminoethanol	ACGIH TLV (United States, 1/2021). Absorbed through skin. TWA: 0.5 ppm 8 hours. TWA: 3.5 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 2 ppm 8 hours. TWA: 14 mg/m³ 8 hours. NIOSH REL (United States, 10/2020). Absorbed through skin. TWA: 2 ppm 10 hours. TWA: 14 mg/m³ 10 hours.
Phosphoric acid, isotridecyl ester	None.
2-amino-2-methylpropanol	None.
Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-	None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

Environmental exposure controls

- Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.

Respiratory protection

: A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Date of issue/Date of revision : 12/1/2022 Date of previous issue : No previous Version : 1 5/12 US



Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Color : Yellow.

Odor : Characteristic. **Odor threshold** : Not available.

pH : 8.8 to 9.6 [Conc. (% w/w): 5%]

Melting point/freezing point : Not available.

: <32°F **Pour point**

Boiling point, initial boiling point, and boiling range

: Not available.

: Open cup: 276.8°F Flash point : Not available. **Evaporation rate** : Not available. **Flammability** Lower and upper explosion : Not available.

limit/flammability limit

: Not available. Vapor pressure **Relative vapor density** : Not available. : Not available. **Relative density** : 0.985 g/cm³ [68°F] **Density** : Not available. Solubility in water Partition coefficient: n-: Not applicable.

octanol/water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available.

Viscosity : Kinematic (104°F): 56.7 mm²/s (56.7 cSt)

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : Shelf life: 12 months.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 12/1/2022 Version 6/12 US Date of previous issue : No previous validation



Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-(methylimino)diethanol	LD50 Dermal	Rabbit	>2000 mg/kg	-
, ,	LD50 Oral	Rat	4780 mg/kg	-
2-dibutylaminoethanol	LD50 Dermal	Rabbit	1680 mg/kg	-
•	LD50 Oral	Rat	1070 mg/kg	-
Phosphoric acid, isotridecyl ester	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-amino-2-methylpropanol	LD50 Dermal	Rabbit	>2000 mg/kg	-
Poly(oxy-1,2-ethanediyl), α- (carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-dibutylaminoethanol	Skin - Severe irritant	Rabbit	-	24 hours 5	-
	Skin - Severe irritant	Rabbit	-	mg 500 mg	-

Conclusion/Summary

Eyes : pH value - Used for classification

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification IARC/OSHA/NTP

Not applicable.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name		Route of exposure	Target organs
2-dibutylaminoethanol	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Date of issue/Date of revision: 12/1/2022Date of previous issue: No previousVersion: 17/12US



Section 11. Toxicological information

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Blaser TP 318 2,2'-(methylimino)diethanol 2-dibutylaminoethanol Phosphoric acid, isotridecyl ester 2-amino-2-methylpropanol Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	12012.8	18531.5	N/A	N/A	N/A
	4780	2500	N/A	N/A	N/A
	1070	1680	N/A	N/A	N/A
	2500	2500	N/A	N/A	N/A
	N/A	2500	N/A	N/A	N/A
	2500	N/A	N/A	N/A	N/A



Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
2-dibutylaminoethanol	Acute EC10 6.9 mg/l	Aquatic plants	72 hours
	Acute EC50 21 mg/l	Aquatic plants	72 hours
	Acute EC50 73.7 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 29 mg/l	Fish	96 hours
	Chronic NOEC 4.4 mg/l	Daphnia	21 days
2-amino-2-methylpropanol	LC50 193 mg/l	Daphnia	48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2,2'-(methylimino)diethanol	-1.08	-	low
2-dibutylaminoethanol	-	<39	low
2-amino-2-methylpropanol	-0.63	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-



Section 14. Transport information

L	1		1	T	1	1
	Environmental	No.	No.	No.	No.	No.
				1	1	1
	hazards					1
						1

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

Clean Air Act Section 112

: Not listed

(b) Hazardous Air **Pollutants (HAPs)**

Clean Air Act Section 602

: Not listed

Class I Substances

Clean Air Act Section 602

: Not listed

Class II Substances

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
2,2'-(methylimino)diethanol	≥10 - ≤25	EYE IRRITATION - Category 2A
2-dibutylaminoethanol	≤3	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Phosphoric acid, isotridecyl ester	<3	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
2-amino-2-methylpropanol	≤3	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z) -9-octadecen-1-yloxy]-	≤3	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1

California Prop. 65

This product contains one or more chemicals listed under California Proposition 65. Such chemicals are not used as raw materials in the product formulation but rather are typical impurities.

California SCAQMD Rule 1144:



Section 15. Regulatory information

Category: Metalworking Fluid – Metal Removal – General. Recordkeeping requirement: Super Compliant. (< 50 g/L VOC @ max. use concentration)

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

List name	Ingredient name	Status
Schedule III	Methyldiethanolamine	Listed
	Triethanolamine	Listed

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Canada : All components are listed or exempted.United States : All components are active or exempted.

Section 16. Other information

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
3 7	Calculation method Expert judgment

History

Date of printing : 12/1/2022 Date of issue/Date of : 12/1/2022

revision

Date of previous issue : No previous validation

Version : 1

Prepared by : Product Stewardship Blaser Swisslube AG

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations



Section 16. Other information

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.