Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET



B-Cool GR 620

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- Product name
- : B-Cool GR 620
- Article No. Product description
- : 11620-01
- : Industrial use only. Metal working fluids

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Industrial use only. Metal working fluids		
	Uses advised against	
Consumer use.		

1.3 Details of the supplier of the safety data sheet

Manufacturer	:	BLASER SWISSLUBE AG Winterseistrasse 22 CH-3415 Hasle-Rüegsau Switzerland
		Tel:+41 (0)34 460 01 01
		E-Mail: contact@blaser.com
Supplier's details	:	Jemtech (UK) Ltd. Bellbrook Industrial Estate Uckfield TN22 1QL East Sussex Tel:+44 1825 767640 E-Mail: sales@jemtech.co.uk
e-mail address of person responsible for this SDS	:	reach@blaser.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number	: 111
<u>Supplier</u>	

Telephone number : +44 1235 239670 (24h/7d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Blaser.

B-Cool GR 620

SECTION 2: Hazards identification

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H315 - Causes skin irritation. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	:	Not applicable.
Prevention	:	P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P264 - Wash thoroughly after handling.
Response	:	 P302 + P352 - IF ON SKIN: Wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	•	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
Alcohols, C16-18, ethoxylated propoxylated	REACH #: Polymer EC: 614-209-5 CAS: 68002-96-0	≥10 - ≤25	Aquatic Chronic 3, H412	[1]
1-aminopropan-2-ol	REACH #: 01-2119475331-43 EC: 201-162-7 CAS: 78-96-6 Index: 603-082-00-1	≤10	Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1]
Distillates (Fischer-Tropsch), heavy, C18-50 branched, cyclic and linear	REACH #: 01-0000020163-82 EC: 482-220-0 CAS: 848301-69-9	≤10	Asp. Tox. 1, H304	[1]
neodecanoic acid	REACH #:	≤10	Acute Tox. 4, H302	[1]

Blaser.

SI 2019/758 B-Cool GR 620				SWI
SECTION 3: Composition	on/information on ing	redients		
2,2'-(cyclohexylimino)bisethanol	01-2119449554-33 EC: 248-093-9 CAS: 26896-20-8 REACH #: 01-2119962183-38 EC: 224-809-5 CAS: 4500-29-2	≤3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 (gastrointestinal tract)	[1]
Poly(oxy-1,2-ethanediyl), α- (carboxymethyl)-ω-(octyloxy)-	UK (GB) REACH #: Polymer REACH #: Polymer CAS: 53563-70-5	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
benzotriazole	REACH #: 01-2119979079-20 EC: 202-394-1 CAS: 95-14-7	≤1.5	Acute Tox. 4, H302 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	[1]
dicyclohexylamine	REACH #: 01-2119493354-33 EC: 202-980-7 CAS: 101-83-7 Index: 612-066-00-3	≤0.89	Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
1,2-Ethanediamine, N1,N1,N2, N2-tetramethyl-, polymer with 1,1'- oxybis[2-chloroethane]	REACH #: Polymer CAS: 31075-24-8	≤0.14	Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	[1]
			See Section 16 for the full text of the H statements declared above.	

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first ai	d measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Avoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/s	symptoms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	-	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	teo	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

SECTION 7: Handling and storage

7.3 Specific end use(s)

Recommendations

- Industrial sector specific solutions
- : Not available.
- : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres -Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
raminopropan-2-ol	DNEL	Long term Inhalation	8.5 mg/m ³	Workers	Systemic
neodecanoic acid	DNEL	Long term Dermal	29 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	86 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	25.79 mg/ m ³	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
1-aminopropan-2-ol	Fresh water Marine water Fresh water sediment Marine water sediment Soil Sewage Treatment Plant	0.0327 mg/l 0.00327 mg/l 0.177 mg/l 0.0177 mg/kg 0.0161 mg/kg 3.3 mg/l	- - - - -

8.2 Exposure controls

controls

: Good general ventilation should be sufficient to control worker exposure to airborne Appropriate engineering contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
Respiratory protection	: A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>			
Physical state	:	Liquid.	
Colour	:	Yellow.	
Odour	:	Amine-like.	
Odour threshold	:	Not available.	
Melting point/freezing point	:	Not available.	
Pour point	:	<0°C	
Initial boiling point and boiling range	:	Not available.	
Flammability (solid, gas)	:	Not available.	
Upper/lower flammability or explosive limits	:	Not available.	
Flash point	:	Open cup: Not applicable.	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	÷	Not available.	
рН	1	8.8 to 9.2 [Conc. (% w/w): 5%]	
Viscosity	:	♥ynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 68.4 mm²/s	
Solubility in water	;	Not available.	
Partition coefficient: n-octanol/ water	:	Not applicable.	
Vapour pressure	:	Not available.	
Date of issue/Date of revision : 28. Fe	b.	2025 Date of previous issue : 1.01	Version

SECTION 9: Physical and chemical properties

Relative density	: Not available.
Density	: 1.021 g/cm³ [20°C (68°F)]
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredient	s.
10.2 Chemical stability	: Shelf life: 24 months.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Alcohols, C16-18,	LD50 Oral	Rat	>2000 mg/kg	-
ethoxylated propoxylated			0.0	
1-aminopropan-2-ol	LD50 Dermal	Rabbit	1851 mg/kg	-
	LD50 Oral	Rat	2098 mg/kg	-
Distillates (Fischer-Tropsch),	LD50 Dermal	Rat	>2000 mg/kg	-
heavy, C18-50 branched,			00	
cyclic and linear				
	LD50 Oral	Rat	>5000 mg/kg	-
neodecanoic acid	LD50 Dermal	Rat	3640 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2,2'-(cyclohexylimino)	LD50 Oral	Rat	>2000 mg/kg	-
bisethanol				
Poly(oxy-1,2-ethanediyl), α-	LD50 Oral	Rat	>2000 mg/kg	-
(carboxymethyl)-ω-(octyloxy)				
-				
benzotriazole	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-
dicyclohexylamine	LD50 Dermal	Rabbit	200 mg/kg	-
	LD50 Oral	Rat	200 mg/kg	-
1,2-Ethanediamine, N1,N1,	LC50 Inhalation Vapour	Rat	5.8 mg/l	4 hours
N2,N2-tetramethyl-,				
polymer with 1,1'-oxybis				
[2-chloroethane]				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1951 mg/kg	-

Conclusion/Summary

: Not available.

SECTION 11: Toxicological information

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
E-Cool GR 620	>2000	>2000	N/A	N/A	N/A
1-aminopropan-2-ol	2098	1851	N/A	N/A	N/A
neodecanoic acid	500	3640	N/A	N/A	N/A
2,2'-(cyclohexylimino)bisethanol	500	N/A	N/A	N/A	N/A
benzotriazole	500	N/A	N/A	N/A	N/A
dicyclohexylamine	200	200	N/A	N/A	N/A
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis[2-chloroethane]	1951	N/A	N/A	11	N/A

Blaser.

Irritation/Corrosion

Not available.

Conclusion/Summary

Conclusion/Summary

Skin	: p	oH value - Used for classification
Eyes	: r	oH value - Used for classification

Eyes **Respiratory or skin sensitization**

Not available.

: Not available.

Mutagenicity

Not available.

Conclusion/Summary : Not available.

Carcinogenicity

Not available.

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
	-	Equivocal		Mammal - species unspecified	Route of exposure unreported	-
Conclusion/Summary	: Not availab	ole.			•	

Conclusion/Summary

Teratogenicity

Not available.

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-(cyclohexylimino)bisethanol	Category 2	-	gastrointestinal tract

Aspiration hazard

Product/ingredient name	Result
Distillates (Fischer-Tropsch), heavy, C18-50 branched, cyclic and linear	ASPIRATION HAZARD - Category 1

Blaser.

B-Cool GR 620

SECTION 11: Toxicological information

Information on likely routes of exposure	:	Not available.
Potential acute health effects	2	
Eye contact	1	Causes serious eye irritation.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes skin irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	sic	al, chemical and toxicological characteristics
Eye contact		Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	4	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effec	ts	as well as chronic effects from short and long-term exposure
Delayed and immediate effec Short term exposure	<u>ts</u>	as well as chronic effects from short and long-term exposure
		as well as chronic effects from short and long-term exposure Not available.
Short term exposure Potential immediate	:	
Short term exposure Potential immediate effects	:	Not available.
Short term exposure Potential immediate effects Potential delayed effects	:	Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate	: :	Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects		Not available. Not available. Not available. Not available.
Short term exposurePotential immediateeffectsPotential delayed effectsLong term exposurePotential immediateeffectsPotential delayed effects		Not available. Not available. Not available. Not available.
Short term exposurePotential immediateeffectsPotential delayed effectsLong term exposurePotential immediateeffectsPotential delayed effectsPotential delayed effectsPotential chronic health effects	: : : ect	Not available. Not available. Not available. Not available.
Short term exposurePotential immediateeffectsPotential delayed effectsLong term exposurePotential immediateeffectsPotential delayed effectsPotential delayed effectsPotential chronic health effectsNot available.	: : : ect	Not available. Not available. Not available. Not available.
Short term exposurePotential immediateeffectsPotential delayed effectsLong term exposurePotential immediateeffectsPotential delayed effectsPotential chronic health effectsNot available.Conclusion/Summary	: : : : : : :	Not available. Not available. Not available. Not available.

Other information

Reproductive toxicity

: Not available.

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
	LC50 >100 mg/l	Fish	96 hours
-	Acute LC50 210 mg/l Fresh water	Fish - Goldfish - Carassius auratus	96 hours
-	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
-	EC50 >100 mg/l	Fish	96 hours
-	LC50 180 mg/l	Fish	96 hours
	Acute EC50 15.8 mg/l	Daphnia - Water flea - Daphnia galeata	48 hours
	Chronic NOEC 1 mg/l	Daphnia - Water flea - Daphnia	21 days

: No known significant effects or critical hazards.

SECTION 12: Ecological information

-	Acute EC50 70.1 mg/l Fresh water	galeata Daphnia - Water flea - Daphnia magna	48 hours
-	Acute EC50 0.37 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0.037 mg/l Fresh water	Fish	96 hours

Blaser.

: Not available. **Conclusion/Summary**

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
p enzotriazole	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
✓-aminopropan-2-ol	-0.96	-	Low
neodecanoic acid	2.1	<225	Low
benzotriazole	1.44	-	Low
dicyclohexylamine	2.724	459	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Hazardous waste

Waste catalogue

Waste code	Waste designation
12 01 10* 12 01 09*	synthetic machining oils machining emulsions and solutions free of halogens
Packaging Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Blaser.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Additional informa	ation		•	·

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC) Not listed.

Persistent Organic Pollutants Not listed.

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable. on the manufacture,

placing on the market

and use of certain

dangerous substances, mixtures and articles

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

List name	Ingredient name	Status
Schedule III	Triethanolamine	Listed

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group wDr8 = Very Persistent and Very Bioaccumulative 	
vPvB = Very Persistent and Very Bioaccumulative Procedure used to derive the classification		

SECTION 16: Other information

Classification	Justification
Skin Irrit. 2, H315	Expert judgment
Eye Irrit. 2, H319	Expert judgment
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

<u>IP346:</u>

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

Date of printing	: 28. Feb. 2025
Date of issue/ Date of revision	: 28. Feb. 2025
Date of previous issue	: 25. Apr. 2024
Version	: 1.02
Prepared by	: Product Stewardship Blaser Swisslube AG

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.