Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



B-Cool Eltec 502

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	
UFI	
Article No.	

: B-Cool Eltec 502

: CYSJ-D438-0213-5KA1

: 11502-01

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Industrial use only. Metal working fluids		
	Uses advised against	
Consumer use.		

1.3 Details of the supplier of the safety data sheet

Manufacturer	(BLASER SWISSLUBE AG Winterseistrasse 22 CH-3415 Hasle-Rüegsau Switzerland Tel:+41 (0)34 460 01 01 E-Mail: contact@blaser.com
Supplier's details	 -	Jemtech (UK) Ltd. Bellbrook Industrial Estate Uckfield TN22 1QL East Sussex Tel:+44 1825 767640 E-Mail: sales@jemtech.co.uk
e-mail address of person responsible for this SDS	: 1	reach@blaser.com

1.4 Emergency telephone number

National advisory body/P	<u>Poison Centre</u>
Telephone number	: 01 809 2566
<u>Supplier</u>	
Telephone number	: +44 1235 239670 (24h/7d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

ŝ

2.2 Label elements



Signal word	:	Warning
Hazard statements	1	H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	P280 - Wear eye or face protection. P273 - Avoid release to the environment.
Response	:	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	1	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

1907/2006, Annex XIIIOther hazards which do: None known.not result in classification

to Regulation (EC) No.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
benzotriazole	REACH #: 01-2119979079-20 EC: 202-394-1 CAS: 95-14-7	≤10	Acute Tox. 4, H302 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg	[1]
Alcohols, C16-18, ethoxylated propoxylated	REACH #: Polymer EC: 614-209-5 CAS: 68002-96-0	≤5	Aquatic Chronic 3, H412	-	[1]
2-amino-2-methylpropanol	REACH #: 01-2119475788-16 EC: 204-709-8 CAS: 124-68-5 Index: 603-070-00-6	≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	-	[1]
pyridine-2-thiol 1-oxide, sodium salt	REACH #: Biocide EC: 223-296-5	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H311	ATE [Oral] = 500 mg/kg	[1]
Date of issue/Date of revision	: 20. Dec. 2023	Date of previ	ous issue : 19. Dec.	2023 Version : 2	2/1



SECTION 3: Composition/information on ingredients

I			5		
	CAS: 3811-73-2		Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 (nervous system) Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH070	ATE [Dermal] = 790 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 100	
2-n-butyl-benzo[d]isothiazol- 3-one	REACH #: Biocide EC: 420-590-7 CAS: 4299-07-4	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 10 M [Chronic] = 1	[1]

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid r	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Avoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Date of issue/Date of revision	: 20. Dec. 2023 Date of previous issue : 19. Dec. 2023 Version : 2 3/14



SECTION 4: First aid measures

4.2 Most important symptom	is and effects, both acute and delayed	
Over-exposure signs/symp	toms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
4.3 Indication of any immedi	ate medical attention and special treatment needed	
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	
SECTION 5: Firefight	ting measures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
5.2 Special hazards arising f	rom the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ective equipment and emergency procedures
For non-emergency : personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders :	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Blaser.

SECTION 6: Accidental release measures

B-Cool Eltec 502

6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.		
6.3 Methods and material	for containment and cleaning up		
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.		
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.		

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) Recommendations Industrial sector specific solutions

- : Not available.
- : Not available.



SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

B-Cool Eltec 502

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures	 Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be
-----------------------------------	---

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.		
Individual protection measur	es			
Hygiene measures	:	Vash hands, forearms and face thoroughly after handling chemical products, efore eating, smoking and using the lavatory and at the end of the working perio oppropriate techniques should be used to remove potentially contaminated cloth Vash contaminated clothing before reusing. Ensure that eyewash stations and afety showers are close to the workstation location.		
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.		
Skin protection				
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).		
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.		
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.		



SECTION 8: Exposure controls/personal protection

Respiratory protection	: A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Yellowish.
Odour	: Amine-like.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Open cup: 174°C
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
рН	: 7.8 to 8.8 [Conc. (% w/w): 5%]
Viscosity	: Kinematic (40°C): 68.6 mm ² /s
Partition coefficient: n-octanol/	: Not applicable.

Dispersibility properties

water

B-Cool Eltec 502

Media	Result	
cold water hot water	Dispersible Dispersible	
Vapour pressure	: Not available.	
Relative density	: Not available.	
Density	: 1.043 g/cm ³ [20	°C]
Vapour density	: Not available.	
Particle characteristics		
Median particle size	: Not applicable.	

9.2.1 Information with regard to physical hazard classes

Oxidising properties : Not available.

9.2.2 Other safety characteristics



SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	Shelf life: 24 months.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzotriazole	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-
Alcohols, C16-18, ethoxylated propoxylated	LD50 Oral	Rat	>2000 mg/kg	-
2-amino-2-methylpropanol	LD50 Dermal	Rabbit	>2000 mg/kg	-
pyridine-2-thiol 1-oxide, sodium salt	LD50 Dermal	Rat	1800 mg/kg	-
	LD50 Oral	Rat	1500 mg/kg	-
2-n-butyl-benzo[d]isothiazol- 3-one	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	4267 to 4732 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
B-Cool Eltec 502	>2000	N/A	N/A	N/A	N/A
benzotriazole	500	N/A	N/A	N/A	N/A
pyridine-2-thiol 1-oxide, sodium salt	500	790	N/A	N/A	0.5

Irritation/Corrosion	
Conclusion/Summary	: Not available.
Sensitisation	
Conclusion/Summary	: Not available.
Mutagenicity	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.

Date of issue/Date of revision



SECTION 11: Toxicological information

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pyridine-2-thiol 1-oxide, sodium salt	Category 1	-	nervous system

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards 11.2.1 Endocrine disrupting properties Not available.

- 11.2.2 Other information
- Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
benzotriazole	LC50 180 mg/l	Fish	96 hours
	Acute EC50 15.8 mg/l	Daphnia - Daphnia galeata	48 hours
	Chronic NOEC 1 mg/l	Daphnia - Daphnia galeata	21 days
Alcohols, C16-18, ethoxylated propoxylated	LC50 >100 mg/l	Fish	96 hours
2-amino-2-methylpropanol	LC50 193 mg/l	Daphnia	48 hours
pyridine-2-thiol 1-oxide, sodium salt	EC50 0.0012 mg/l	Algae	72 hours
	EC50 0.0088 mg/l	Daphnia	48 hours
2-n-butyl-benzo[d]isothiazol- 3-one	EC50 0.45 mg/l	Algae	72 hours
	EC50 0.093 mg/l	Daphnia	48 hours
	LC50 0.15 mg/l	Fish	96 hours
Conclusion/Summary	: Not available.		÷

12.2 Persistence and degradability

Conclusion/Summary	: Not available.
--------------------	------------------

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzotriazole	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzotriazole	1.44	-	Low
2-amino-2-methylpropanol	-0.63		Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Blaser.



SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Hazardous waste

European waste catalogue (EWC)

Waste code	Waste designation	
12 01 07* 12 01 09*	mineral-based machining oils free of halogens (except emulsions and solutions) machining emulsions and solutions free of halogens	
Packaging		
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Not available. 14.7 Maritime transport in bulk according to IMO instruments



B-Cool Eltec 502 SECTION 15: Regulatory information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations **Industrial emissions** : Not listed (integrated pollution prevention and control) -Air Industrial emissions : Not listed (integrated pollution prevention and control) -Water Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. **Persistent Organic Pollutants** Not listed **Seveso Directive** This product is not controlled under the Seveso Directive. International regulations **Chemical Weapon Convention List Schedules I, II & III Chemicals** List name Ingredient name Schedule III Triethanolamine **Montreal Protocol** Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. **Rotterdam Convention on Prior Informed Consent (PIC)** Not listed. **UNECE Aarhus Protocol on POPs and Heavy Metals** Not listed. **15.2 Chemical safety** : No Chemical Safety Assessment has been carried out. assessment

Status

Listed



SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH070	Toxic by eye contact.

Full text of classifications [CLP/GHS]

	ACUTE TOXICITY - Category 3
	ACUTE TOXICITY - Category 4
Aquatic Acute 1 S	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1 L	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2 L	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3 L	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1 S	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2 S	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B S	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2 S	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1 S	SKIN SENSITISATION - Category 1
STOT RE 1 S	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of printing	: 20. Dec. 2023
Date of issue/ Date of	: 20. Dec. 2023
revision	
Date of previous issue	: 19. Dec. 2023
Version	: 2
Responsible name	: Product Stewardship Blaser Swisslube AG
Notice to reader	



SECTION 16: Other information

B-Cool Eltec 502

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.