# SAFETY DATA SHEET

# according to UN-GHS (rev. 7)



Synergy DWS 300

Section 1. Identif	ication
Product identifier	: Synergy DWS 300
Article No.	: 17300-01
Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	
Industrial use only. Metal working fluids	
Uses advised against	
Consumer use.	
Manufacturer	: BLASER SWISSLUBE AG Winterseistrasse 22 CH-3415 Hasle-Rüegsau Switzerland Tel:+41 (0)34 460 01 01 E-Mail: contact@blaser.com
Supplier's details	<ul> <li>Hi-Tech Machine Tools (Pty) Ltd 16 Nguni Drive ,Longmeadow West Modderfontein,1609 South Africa Tel:+27 (0) 11 608 0088</li> <li>E-Mail: info@hitech.co.za</li> </ul>
e-mail address of person responsible for this SDS	: reach@blaser.com
Emergency telephone number (with hours of operation)	: +27 21 300 2732 (24h/7d)
Section 2. Hazard	lidentification
Classification of the substance or mixture	: ACUTE TOXICITY (dermal) - Category 5 ACUTE TOXICITY (inhalation) - Category 5 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>H313 + H333 - May be harmful in contact with skin or if inhaled.</li> <li>H315 - Causes skin irritation.</li> <li>H319 - Causes serious eye irritation.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
General	: Not applicable.
Date of issue/Date of revision	: 20. Dec. Date of previous issue : 16. Dec. 2022 Version : 2 1/13 ZA 2023



# Section 2. Hazard identification

Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> <li>P264 - Wash thoroughly after handling.</li> </ul>
Response	<ul> <li>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P312 + P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. P332 + P313 - If skin irritation occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.</li> </ul>
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
2,2',2"-nitrilotriethanol	≥25 - ≤30	102-71-6
1-(N,N-bis(2-hydroxyethyl)amino)propan-2-ol	≥10 - ≤20	6712-98-7
neodecanoic acid	≤10	26896-20-8
2-aminoethanol	≤5	141-43-5
sodium hydroxide	≤3	1310-73-2
citric acid	≤3	5949-29-1
benzotriazole	≤3	95-14-7
pyridine-2-thiol 1-oxide, sodium salt	≤0.3	3811-73-2
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	≤0.1	31075-24-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

**Description of necessary first aid measures** 

- Eye contact
- : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.



# Section 4. First aid measures

Inhalation	: Avoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

MOSt important symptoms/	enects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: May be harmful if inhaled.
Skin contact	: May be harmful in contact with skin. Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sym</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li> <li>The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

#### See toxicological information (Section 11)

thoroughly with water before removing it, or wear gloves.



# Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# Section 6. Accidental release measures

## procedures

<u>reisonal precautions, protec</u>	uv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and material for con	ntai	inment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	-	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.



# Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general soccupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: -15 to 40°C (5 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

## Control parameters

## **Occupational exposure limits**

Ingredient name	Exposure limits		
2,2',2"-nitrilotriethanol	DOL OEL (South Africa, 3/2021). Notes: Occupational exposure limit – restricted limit TWA: 10 mg/m <sup>3</sup> 8 hours.		
2-aminoethanol	DOL OEL (South Africa, 8/1995). Notes: Recommended limit TWA: 8 mg/m <sup>3</sup> 8 hours. TWA: 3 ppm 8 hours. STEL: 15 mg/m <sup>3</sup> 15 minutes. STEL: 6 ppm 15 minutes.		
sodium hydroxide	DOL OEL (South Africa, 8/1995). Notes: Recommended limit STEL: 2 mg/m <sup>3</sup> 15 minutes.		

#### **Biological exposure indices**

No exposure indices known.

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Date of issue/Date of revision         : 20. Dec.         Date of previous issue           2023         2023	: 16. Dec. 2022	Version : 2	5/13 ZA
--	-----------------	-------------	---------



# Section 8. Exposure controls/personal protection

Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum).
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
Respiratory protection	:	A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Relative density	: Not available. : 20. Dec. Date of previous issue : 16. Dec. 2022	Version : 2	6/13 ZA
Relative vapour density	: Not available.		
Vapour pressure	: Not available.		
Lower and upper explosion limit/ flammability limit	: Not available.		
Flammability	: Not available.		
Evaporation rate	: Not available.		
Flash point	: Open cup: Not applicable.		
Boiling point, initial boiling point, and boiling range	: Not available.		
Pour point	: <0°C (<32°F)		
Melting point/freezing point	: Not available.		
рН	: 8.7 to 9.4 [Conc. (% w/w): 5%]		
Odour threshold	: Not available.		
Odour	: Amine-like.		
Colour	: Light tan.		
Physical state	: Liquid.		



# Section 9. Physical and chemical properties and safety characteristics

Density Solubility in water	: 1.105 g/cm³ [20°C (68°F)] : Not available.
Miscible with water	: Yes.
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 10.3 mm²/s (10.3 cSt)
Particle characteristics	
Median particle size	: Not applicable.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Shelf life: 24 months.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

## Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure
2,2',2"-nitrilotriethanol	LD50 Dermal		Rabbit	>2000 mg/kg	-
	LD50 Oral		Rat	6400 mg/kg	-
1-(N,N-bis(2-hydroxyethyl) amino)propan-2-ol	LD50 Dermal		Rabbit	>2000 mg/kg	-
	LD50 Oral		Rat	>2000 mg/kg	-
neodecanoic acid	LD50 Dermal		Rat	3640 mg/kg	-
	LD50 Oral		Rat	>2000 mg/kg	-
2-aminoethanol	LD50 Dermal		Rabbit	2504 mg/kg	-
	LD50 Oral		Rat	1720 mg/kg	-
sodium hydroxide	LD50 Oral		Rat	>2000 mg/kg	-
citric acid	LD50 Dermal		Rabbit	>2000 mg/kg	-
benzotriazole	LD50 Dermal		Rabbit	>2000 mg/kg	-
ate of issue/Date of revision	: 20. Dec. 2023	Date of previous iss	ue :	16. Dec. 2022 Ver	sion:2 7/13 Z



# Section 11. Toxicological information

	-			
	LD50 Oral	Rat	500 mg/kg	-
pyridine-2-thiol 1-oxide, sodium salt	LD50 Dermal	Rat	1800 mg/kg	-
	LD50 Oral	Rat	1500 mg/kg	-
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	LC50 Inhalation Vapour	Rat	5.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1951 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-aminoethanol	Skin - Severe irritant	Woman	-	-	-
citric acid	Eyes - Mild irritant	Rabbit	-	0.5 minutes 5 mg	-

## **Conclusion/Summary**

#### Skin

Eyes

### : pH value - Used for classification : pH value - Used for classification

**Sensitisation** 

Not available.

## **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)


Product/ingredient name	• •	Route of exposure	Target organs
2-aminoethanol	Category 3	-	Respiratory tract irritation
citric acid	Category 3	-	Respiratory tract irritation

## Specific target organ toxicity (repeated exposure)

Product/ingredient name		Route of exposure	Target organs
pyridine-2-thiol 1-oxide, sodium salt	Category 1	-	nervous system

## **Aspiration hazard**

Not available.



VISSLUBE

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

## Numerical measures of toxicity

## Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Synergy DWS 300	N/A	4179.0	N/A	N/A	N/A
2,2',2"-nitrilotriethanol	6400	2500	N/A	N/A	N/A
1-(N,N-bis(2-hydroxyethyl)amino)propan-2-ol	2500	2500	N/A	N/A	N/A
neodecanoic acid	2500	3640	N/A	N/A	N/A
2-aminoethanol	1720	1100	N/A	11	N/A
sodium hydroxide	500	N/A	N/A	N/A	N/A
Date of issue/Date of revision : 20. Dec. Date 2023	e of previous issue	: 16.	Dec. 2022	Version : 2	9/13 ZA

. ..



# Section 11. Toxicological information

benzotriazole	500	2500	N/A	N/A	N/A
pyridine-2-thiol 1-oxide, sodium salt	500	790	N/A	N/A	0.5
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis[2-chloroethane]	1951	2500	N/A	11	N/A

# Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
2,2',2"-nitrilotriethanol	Chronic NOEC 16 mg/l Fresh water	Daphnia - Daphnia magna	21 days
1-(N,N-bis(2-hydroxyethyl) amino)propan-2-ol	EC50 >100 mg/l	Aquatic plants	96 hours
	EC50 >100 mg/l	Daphnia	48 hours
neodecanoic acid	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
2-aminoethanol	Acute LC50 329160 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Chronic NOEC 0.85 mg/l	Daphnia	21 days
	Chronic NOEC 1.2 mg/l	Fish	30 days
benzotriazole	LC50 180 mg/l	Fish	96 hours
	Acute EC50 15.8 mg/l	Daphnia - <i>Daphnia galeata</i>	48 hours
	Chronic NOEC 1 mg/l	Daphnia - <i>Daphnia galeata</i>	21 days
pyridine-2-thiol 1-oxide, sodium salt	EC50 0.0012 mg/l	Algae	72 hours
	EC50 0.0088 mg/l	Daphnia	48 hours
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	Acute EC50 0.37 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0.037 mg/l Fresh water	Fish	96 hours

## Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-(N,N-bis(2-hydroxyethyl) amino)propan-2-ol	-	86%; < 28 day(s)	-
benzotriazole	-	-	Not readily

## **Bioaccumulative potential**

Date of issue/Date of revision

Section 12	Ecological information
Section 12.	Ecological information

Product/ingredient name	LogPow	BCF	Potential
2,2',2"-nitrilotriethanol	-1	<3.9	Low
neodecanoic acid	2.1	<225	Low
2-aminoethanol	-1.31	-	Low
citric acid	-1.72	-	Low
benzotriazole	1.44	-	Low

## **Mobility in soil**

Soil/water partition	: Not available.
coefficient (Koc)	

#### Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or
	liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

•			
	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments





# Section 15. Regulatory information

## 15.1 International regulations

Stockholm Convention on Persistent Organic Pollutants Not listed.

## 15.2 Other regulations

Chemical safety assessment : No Chemical Safety Assessment has been carried out.

## Section 16. Other information

<u>History</u>	
Date of printing	: 20. Dec. 2023
Date of issue/Date of revision	: 20. Dec. 2023
Date of previous issue	: 16. Dec. 2022
Version	: 2
Prepared by	: Product Stewardship Blaser Swisslube AG
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor EC50 = Half maximal effective concentration GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LC50 = Median lethal concentration LD50 = Median lethal dose LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available UN = United Nations</li> </ul>

#### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (dermal) - Category 5	Calculation method
ACUTE TOXICITY (inhalation) - Category 5	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Expert judgment
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	Expert judgment
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Calculation method

References

: Not available.

## ✓ Indicates information that has changed from previously issued version.

## Other Regulations:

## **REACH**:

Herewith, we confirm that all our products fulfill all the requirements of REACH regulation. All of the raw materials used in our products are either REACH registered or exempt from registration.

#### **ROHS**:

BLASER Swisslube products are fully compliant with Annex II of DIRECTIVE 2015/863/EU (RoHS 3) and do not contain the following substances above their respective limitations:

Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP), chromium Cr<sup>6</sup>+-compounds, Heavy metals (Lead or it's compounds, cadmium or it's compounds, mercury or it's compounds).

Herewith we confirm that, with the exceptions of Additive A38 (art.-no. 29182-02), our cutting and grinding fluids do not contain any Substances of Very High Concern (SVHC) above the regulatory cut-off limit of 0.1%.



# Section 16. Other information

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.