

SAFETY DATA SHEET



B-Cool GR 620

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : B-Cool GR 620
UFI : 6SK3-FGNH-T21A-S70X
Article No. : 11620-01
Product description : Industrial use only.
Metal working fluids

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use only. Metal working fluids
Uses advised against
Consumer use.

1.3 Details of the supplier of the safety data sheet

Manufacturer : BLASER SWISSLUBE AG
Winterseistrasse 22
CH-3415 Hasle-Rüegsau
Switzerland
Tel: +41 (0)34 460 01 01
E-Mail: contact@blaser.com

Tel:

e-mail address of person responsible for this SDS : reach@blaser.com

1.4 Emergency telephone number

National advisory body/Poison Centre

: 145 (from abroad: +41 44 251 51 51)
Information: +41 44 251 66 66

Telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

☒ Skin Irrit. 2, H315
Eye Irrit. 2, H319
Repr. 2, H361f
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

B-Cool GR 620

SECTION 2: Hazards identification

Hazard pictograms	: 
Signal word	: Warning
Hazard statements	: H315 - Causes skin irritation. H319 - Causes serious eye irritation. H361f - Suspected of damaging fertility. H412 - Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
Prevention	: P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P273 - Avoid release to the environment. P264 - Wash thoroughly after handling.
Response	: P308 + P313 - IF exposed or concerned: Get medical advice or attention. P302 + P352 - IF ON SKIN: Wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2,2',2''-nitrilotriethanol	REACH #: 01-2119486482-31 EC: 203-049-8 CAS: 102-71-6	≥10 - ≤15	Not classified.	-	[2]
Alcohols, C16-18, ethoxylated propoxylated	REACH #: Polymer EC: 614-209-5 CAS: 68002-96-0	≥10 - ≤15	Aquatic Chronic 3, H412	-	[1]
1-aminopropan-2-ol	REACH #: 01-2119475331-43	≤10	Acute Tox. 4, H312 Skin Corr. 1B, H314	ATE [Dermal] = 1851 mg/kg	[1]

B-Cool GR 620

SECTION 3: Composition/information on ingredients

	EC: 201-162-7 CAS: 78-96-6 Index: 603-082-00-1		Eye Dam. 1, H318 Repr. 2, H361f		
Distillates (Fischer-Tropsch), heavy, C18-50 branched, cyclic and linear	REACH #: 01-0000020163-82 EC: 482-220-0 CAS: 848301-69-9	≤10	Asp. Tox. 1, H304	-	[1]
neodecanoic acid	REACH #: 01-2119449554-33 EC: 248-093-9 CAS: 26896-20-8	≤10	Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1]
2,2'-(cyclohexylimino) bisethanol	REACH #: 01-2119962183-38 EC: 224-809-5 CAS: 4500-29-2	≤3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 (gastrointestinal tract)	ATE [Oral] = 500 mg/kg	[1]
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-(octyloxy)-	REACH #: Polymer CAS: 53563-70-5	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318	-	[1]
benzotriazole	REACH #: 01-2119979079-20 EC: 202-394-1 CAS: 95-14-7	≤1.5	Acute Tox. 4, H302 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg	[1]
dicyclohexylamine	REACH #: 01-2119493354-33 EC: 202-980-7 CAS: 101-83-7 Index: 612-066-00-3	≤0.85	Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 200 mg/kg ATE [Dermal] = 200 mg/kg M [Acute] = 1 M [Chronic] = 1	[1]
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	REACH #: Polymer CAS: 31075-24-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1951 mg/kg ATE [Inhalation (vapours)] = 11 mg/l M [Acute] = 10 M [Chronic] = 10	[1]

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : ☒ Avoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : ☒ Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : ☒ Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : ☒ Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : ☒ Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.


For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill :  Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

B-Cool GR 620

SECTION 6: Accidental release measures

- 6.4 Reference to other sections
- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures
- : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations
- : Not available.
- Industrial sector specific solutions
- : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2,2',2''-nitriлотriethanol	SUVA (Switzerland, 1/2023) STEL 15 minutes: 5 mg/m³. Form: Inhalable fraction. TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

Biological exposure indices

No exposure indices known.

- Recommended monitoring procedures
- : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

B-Cool GR 620

SECTION 8: Exposure controls/personal protection

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
1-aminopropan-2-ol neodecanoic acid	DNEL	Long term Inhalation	8.5 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	29 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	86 mg/m³	Workers	Systemic
	DNEL	Long term Oral	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	25.79 mg/ m³	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
1-aminopropan-2-ol	Fresh water	0.0327 mg/l	-
	Marine water	0.00327 mg/l	-
	Fresh water sediment	0.177 mg/l	-
	Marine water sediment	0.0177 mg/kg	-
	Soil	0.0161 mg/kg	-
	Sewage Treatment	3.3 mg/l	-
	Plant		

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm (minimum) .

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.

SECTION 8: Exposure controls/personal protection


- Respiratory protection** : A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Yellow.
- Odour** : Amine-like.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Pour point** : <0°C
- Boiling point or initial boiling point and boiling range** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit** : Not available.
- Flash point** : Open cup: Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- pH** : 8.8 to 9.2 [Conc. (% w/w): 5%]
- Viscosity** :  Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): 68.4 mm²/s
- Solubility** :
Not available.

Solubility in water : Not available.

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Dispersibility properties :

Media	Result
cold water hot water	Dispersible Dispersible

Vapour pressure : Not available.

Relative density : Not available.

Density : 1.021 g/cm³ [20°C]

Relative vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

B-Cool GR 620

SECTION 9: Physical and chemical properties

Oxidising properties : Not available.

9.2.2 Other safety characteristics

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Shelf life: 24 months.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Alcohols, C16-18, ethoxylated propoxylated 1-aminopropan-2-ol	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	1851 mg/kg	-
	LD50 Oral	Rat	2098 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Distillates (Fischer-Tropsch), heavy, C18-50 branched, cyclic and linear	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	3640 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
neodecanoic acid	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2,2'-(cyclohexylimino) bisethanol	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-(octyloxy) - benzotriazole	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-
	LD50 Dermal	Rabbit	200 mg/kg	-
dicyclohexylamine	LD50 Oral	Rat	200 mg/kg	-
	LD50 Oral	Rat	200 mg/kg	-
	LD50 Oral	Rat	200 mg/kg	-
	LD50 Oral	Rat	200 mg/kg	-
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	LC50 Inhalation Vapour	Rat	5.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1951 mg/kg	-
	LD50 Oral	Rat	1951 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

B-Cool GR 620

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
B-Cool GR 620	>2000	>2000	N/A	N/A	N/A
1-aminopropan-2-ol	2098	1851	N/A	N/A	N/A
neodecanoic acid	500	3640	N/A	N/A	N/A
2,2'-(cyclohexylimino)bisethanol	500	N/A	N/A	N/A	N/A
benzotriazole	500	N/A	N/A	N/A	N/A
dicyclohexylamine	200	200	N/A	N/A	N/A
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis[2-chloroethane]	1951	N/A	N/A	11	N/A

Irritation/Corrosion

Conclusion/Summary

Skin : pH value - Used for classification

Eyes : pH value - Used for classification

Respiratory or skin sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
1-aminopropan-2-ol	-	Equivocal	-	Mammal - species unspecified	Route of exposure unreported	-

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-(cyclohexylimino)bisethanol	Category 2	-	gastrointestinal tract

Aspiration hazard

Product/ingredient name	Result
Distillates (Fischer-Tropsch), heavy, C18-50 branched, cyclic and linear	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

SECTION 11: Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : ☒ Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : ☒ Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : ☒ Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : ☒ Suspected of damaging fertility.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

B-Cool GR 620

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Alcohols, C16-18, ethoxylated propoxylated 1-aminopropan-2-ol neodecanoic acid 2,2'-(cyclohexylimino) bisethanol benzotriazole dicyclohexylamine 1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	LC50 >100 mg/l	Fish	96 hours
	Acute LC50 210 mg/l Fresh water	Fish - <i>Carassius auratus</i>	96 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	EC50 >100 mg/l	Fish	96 hours
	LC50 180 mg/l	Fish	96 hours
	Acute EC50 15.8 mg/l	Daphnia - <i>Daphnia galeata</i>	48 hours
	Chronic NOEC 1 mg/l	Daphnia - <i>Daphnia galeata</i>	21 days
	Acute EC50 70.1 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute EC50 0.37 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0.037 mg/l Fresh water	Fish	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzotriazole	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1-aminopropan-2-ol	-0.96	-	Low
neodecanoic acid	2.1	<225	Low
benzotriazole	1.44	-	Low
dicyclohexylamine	2.724	459	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

B-Cool GR 620

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 01 10*	synthetic machining oils
12 01 09*	machining emulsions and solutions free of halogens

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

B-Cool GR 620

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
B-Cool GR 620	≥90	3

Labelling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Storage class (TRGS 510) : 12

VOC content : Exempt.

SZID : 653974-01

Hazardous liquids for water : Class A

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

List name	Ingredient name	Status
Schedule III	Triethanolamine	Listed

Montreal Protocol

Not listed.

B-Cool GR 620

SECTION 15: Regulatory information

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361f Aquatic Chronic 3, H412	Expert judgment Expert judgment Calculation method Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

B-Cool GR 620

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

IP346:

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

Date of printing	: 28. Feb 2025
Date of issue/ Date of revision	: 28. Feb. 2025
Date of previous issue	: 26. Apr. 2024
Version	: 3
Responsible name	: Product Stewardship Blaser Swissslube AG

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.