

SAFETY DATA SHEET



Blasocut BC 40 Strong SW

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Blasocut BC 40 Strong SW
UFI : 5VVG-4DEK-G008-JRX0
Article No. : 01400-61
Product description : Industrial use only.
Metal working fluids

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use only. Metal working fluids
Uses advised against
Consumer use.

1.3 Details of the supplier of the safety data sheet

Manufacturer : BLASER SWISSLUBE AG
Winterseistrasse 22
CH-3415 Hasle-Rüegsau
Switzerland
Tel: +41 (0)34 460 01 01
E-Mail: contact@blaser.com

e-mail address of person responsible for this SDS : reach@blaser.com

1.4 Emergency telephone number

National advisory body/Poison Centre

: 145 (from abroad: +41 44 251 51 51)
Information: +41 44 251 66 66

Telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Blasocut BC 40 Strong SW

SECTION 2: Hazards identification

Hazard pictograms	: 
Signal word	: Warning
Hazard statements	: H319 - Causes serious eye irritation.
Precautionary statements	
Prevention	: P280 - Wear eye or face protection.
Response	: P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-phenoxypropan-2-ol	REACH #: 01-2119486566-23 EC: 212-222-7 CAS: 770-35-4	≤10	Eye Irrit. 2, H319	-	[1]
Sulfonic acids, petroleum, sodium salts	REACH #: 01-2119527859-22 EC: 271-781-5 CAS: 68608-26-4	≤10	Eye Irrit. 2, H319	-	[1]
2,2'-(methylimino)diethanol	REACH #: 01-2119488970-24 EC: 203-312-7 CAS: 105-59-9	≤5	Eye Irrit. 2, H319	-	[1]
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen-1-yloxy]-	REACH #: Exempt CAS: 57635-48-0	≤3	Eye Dam. 1, H318	-	[1]
2-amino-2-methylpropanol	REACH #: 01-2119475788-16 EC: 204-709-8 CAS: 124-68-5 Index: 603-070-00-6	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	-	[1]

Blasocut BC 40 Strong SW

SECTION 3: Composition/information on ingredients

2-aminobutan-1-ol	REACH #: 01-2119492338-28 EC: 202-488-2 CAS: 96-20-8	<1	Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg M [Acute] = 1	[1]
pyridine-2-thiol 1-oxide, sodium salt	REACH #: Biocide EC: 223-296-5 CAS: 3811-73-2	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 (nervous system) Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH070	ATE [Oral] = 500 mg/kg ATE [Dermal] = 790 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 100	[1] [2]
2-n-butyl-benzo[d]isothiazol-3-one	CAS: 4299-07-4 Index: 606-079-00-3	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 10 M [Chronic] = 1	[1]

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact**
 - : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation**
 - : Avoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact**
 - : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
carbonyl halides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures


6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** :  Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.


SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

 Store between the following temperatures: -70 to 40°C (-94 to 104°F). Shelf life: (minimum) 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.

Blasocut BC 40 Strong SW

SECTION 7: Handling and storage

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
pyridine-2-thiol 1-oxide, sodium salt	SUVA (Switzerland, 1/2023) [Natriumpyrithion] Absorbed through skin. TWA 8 hours: 0.2 mg/m³. Form: Inhalable fraction. STEL 15 minutes: 0.4 mg/m³. Form: Inhalable fraction.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm

Blasocut BC 40 Strong SW


SECTION 8: Exposure controls/personal protection

	(minimum) .
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved before handling this product.
Respiratory protection	: A respirator is not needed under normal and intended conditions of product use. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>							
Physical state	: Liquid.						
Colour	: Brown.						
Odour	: Agreeable.						
Odour threshold	: Not available.						
Melting point/freezing point	: Not available.						
Pour point	: <-30°C						
Boiling point or initial boiling point and boiling range	: Not available.						
Flammability	: Not available.						
Lower and upper explosion limit	: Not available.						
Flash point	:  Open cup: 134°C (273.2°F)						
Auto-ignition temperature	: Not available.						
Decomposition temperature	: Not available.						
pH	: 8.5 to 9.2 [Conc. (% w/w): 5%]						
Viscosity	:  Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 75 mm²/s						
Solubility	:						
Not available.							
Solubility in water	: Not available.						
Partition coefficient n-octanol/ water (log Pow)	: Not applicable.						
Dispersibility properties	:						
<table><tr><th>Media</th><th>Result</th></tr><tr><td>cold water</td><td>Dispersible</td></tr><tr><td>hot water</td><td>Dispersible</td></tr></table>		Media	Result	cold water	Dispersible	hot water	Dispersible
Media	Result						
cold water	Dispersible						
hot water	Dispersible						
Vapour pressure	: Not available.						
Relative density	: Not available.						
Density	:  0.97 g/cm³ [20°C]						
Relative vapour density	: Not available.						
<u>Particle characteristics</u>							

Blasocut BC 40 Strong SW

SECTION 9: Physical and chemical properties

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Shelf life: (minimum) 24 months.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1-phenoxypropan-2-ol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
Sulfonic acids, petroleum, sodium salts	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5 g/kg	-
2,2'-(methylimino)diethanol	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4780 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
Poly(oxy-1,2-ethanediyl), α-(carboxymethyl)-ω-[(9Z)-9-octadecen-1-yloxy]-	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rabbit	1800 mg/kg	-
	LD50 Oral	Rat - Female	1208 mg/kg	-
2-amino-2-methylpropanol	LD50 Dermal	Rat	>2000 mg/kg	-
pyridine-2-thiol 1-oxide, sodium salt	LD50 Dermal	Rat	>2000 mg/kg	-
2-n-butyl-benzo[d]isothiazol-3-one	LD50 Oral	Rat	1208 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Blasocut BC 40 Strong SW

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1-phenoxypropan-2-ol	2830	N/A	N/A	N/A	N/A
2,2'-(methylimino)diethanol	4780	N/A	N/A	N/A	N/A
2-aminobutan-1-ol	500	N/A	N/A	N/A	N/A
pyridine-2-thiol 1-oxide, sodium salt	500	790	N/A	N/A	0.5

Irritation/Corrosion

Conclusion/Summary

- Skin : pH value - Used for classification
- Eyes : pH value - Used for classification

Respiratory or skin sensitization

- Conclusion/Summary : Not available.

Mutagenicity

- Conclusion/Summary : Not available.

Carcinogenicity

- Conclusion/Summary : Not available.

Reproductive toxicity

- Conclusion/Summary : Not available.

Teratogenicity

- Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pyridine-2-thiol 1-oxide, sodium salt	Category 1	-	nervous system

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact : Causes serious eye irritation.
- Inhalation : No known significant effects or critical hazards.
- Skin contact : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation : No specific data.
- Skin contact : No specific data.
- Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Blasocut BC 40 Strong SW

SECTION 11: Toxicological information

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1-phenoxypropan-2-ol	EC50 >100 mg/l	Algae	96 hours
	EC50 220 to 460 mg/l	Fish	96 hours
	LC50 370 mg/l	Daphnia	48 hours
2-amino-2-methylpropanol	LC50 193 mg/l	Daphnia	48 hours
	EC50 0.0012 mg/l	Algae	72 hours
pyridine-2-thiol 1-oxide, sodium salt	EC50 0.0088 mg/l	Daphnia	48 hours
	Acute EC50 0.45 mg/l	Algae	72 hours
2-n-butyl-benzo[d]isothiazol-3-one	Acute EC50 0.093 mg/l	Daphnia	48 hours
	Acute LC50 0.15 mg/l	Fish	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1-phenoxypropan-2-ol	1.41	-	Low
2,2'-(methylimino)diethanol	-1.08	-	Low
2-amino-2-methylpropanol	-0.63	-	Low
2-aminobutan-1-ol	-0.45	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Blasocut BC 40 Strong SW

SECTION 12: Ecological information

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 01 06*	mineral-based machining oils containing halogens (except emulsions and solutions)
12 01 08*	
	machining emulsions and solutions containing halogens

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-

Blasocut BC 40 Strong SW

SECTION 14: Transport information

14.5 Environmental hazards	No.	No.	No.	No.
-------------------------------	-----	-----	-----	-----

14.6 Special precautions for user : Transport within user’s premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed above the relevant limit.

[Substances of very high concern](#)

None of the components are listed above the relevant limit.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	%	Designation [Usage]
Blasocut BC 40 Strong SW	≥90	3

Labelling : Not applicable.

[Other EU regulations](#)

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

[Prior Informed Consent \(PIC\) \(649/2012/EU\)](#)

Not listed.

[Persistent Organic Pollutants](#)

Not listed.

[Seveso Directive](#)

This product is not controlled under the Seveso Directive.

[National regulations](#)

Storage class (TRGS 510) : 10

VOC content : Exempt.


SZID : 303402-43

Hazardous liquids for water : Class A

Blasocut BC 40 Strong SW

SECTION 15: Regulatory information

[International regulations](#)
[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)


List name	Ingredient name	Status
 Schedule III	Methyldiethanolamine	Listed

[Montreal Protocol](#)
Not listed.


[Stockholm Convention on Persistent Organic Pollutants](#)
Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)
Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)
Not listed.

15.2 Chemical safety assessment :  This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information


 Indicates information that has changed from previously issued version.

[Abbreviations and acronyms](#) : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Eye Irrit. 2, H319	Expert judgment

[Full text of abbreviated H statements](#)

	H302	Harmful if swallowed.
	H311	Toxic in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H331	Toxic if inhaled.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.
	EUH070	Toxic by eye contact.

[Full text of classifications \[CLP/GHS\]](#)

Blasocut BC 40 Strong SW

SECTION 16: Other information

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

IP346:

The contained refined mineral oils are exempt of labelling. The content of polycyclic aromatic hydrocarbons (PCA) according to IP346 is < 3% (DMSO-extract).

Date of printing : 11. Dec 2024
Date of issue/ Date of revision : 11. Dec. 2024
Date of previous issue : 26. Apr. 2024
Version : 1.02
Responsible name : Product Stewardship Blaser Swisslube AG

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.