Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Switzerland

SAFETY DATA SHEET



Synergy 735

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	: Synergy 735
UFI	: 🗾 🕅 🖉 24D-8TQM-G21S-G7CQ
Article No.	: 11735-03
Product description	: Industrial use only. Metal working fluids

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Industrial use only. Metal working fluids		
	Uses advised against	
Consumer use.		

1.3 Details of the supplier of the safety data sheet

Manufacturer	: BLASER SWISSLUBE AG Winterseistrasse 22 CH-3415 Hasle-Rüegsau Switzerland Tel:+41 (0)34 460 01 01 E-Mail: contact@blaser.com
	Tel:
e-mail address of person responsible for this SDS	: reach@blaser.com

1.4 Emergency telephone number

National advisory body/Poison Centre

: 145 (from abroad: +41 44 251 51 51) Information: +41 44 251 66 66

Telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture **Product definition**

: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Blaser. SWISSLUBE

Synergy 735

SECTION 2: Hazards identification

Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 - Causes skin irritation. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P264 - Wash thoroughly after handling.
Response	 P302 + P352 - IF ON SKIN: Wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2,2',2"-nitrilotriethanol	REACH #: 01-2119486482-31 EC: 203-049-8 CAS: 102-71-6	≥10 - ≤15	Not classified.	-	[2]
neodecanoic acid	REACH #: 01-2119449554-33 EC: 248-093-9 CAS: 26896-20-8	≤10	Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1]
2,2'-(cyclohexylimino) bisethanol	REACH #: 01-2119962183-38 EC: 224-809-5 CAS: 4500-29-2	<5	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 (gastrointestinal tract)	ATE [Oral] = 500 mg/kg	[1]



SECTION 3: Composition/information on ingredients

•			<u> </u>		
3,5,5-trimethylhexanoic acid	REACH #: 01-2119517580-45 EC: 221-975-0 CAS: 3302-10-1	≤5	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg	[1]
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	REACH #: Polymer CAS: 31075-24-8	<0.25	Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1951 mg/kg ATE [Inhalation (vapours)] = 11 mg/ I M [Acute] = 10 M [Chronic] = 10	[1]
			See Section 16 for the full text of the H statements declared above.		

Additional information :

Neutralisation product: Equilibrium of Ionic Pairs according to REACH Annex V, 4.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Check for and remove any contact lenses. Get medical attention.
Inhalation	: Kvoid breathing vapour or mist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

Date of issue/Date of revision	: 4. Mar. 2025	Date of previous issue	:16. Jul. 2024	Version : 7	3/14
--------------------------------	----------------	------------------------	----------------	-------------	------

SECTION 4: First aid measures

	pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed.
The exposed person may need to be kept under medical surveillance for 48 hours.Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	 If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

4/14

Blaser.



SECTION 6: Accidental release measures

6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material	for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 40°C (32 to 104°F). Shelf life: 24 months. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	



SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
₽,2',2"-nitrilotriethanol	SUVA (Switzerland, 1/2023) STEL 15 minutes: 5 mg/m³. Form: Inhalable fraction. TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
neodecanoic acid	DNEL	Long term Dermal	29 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	86 mg/m³	Workers	Systemic
	DNEL	Long term Oral	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	17.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	25.79 mg/ m ³	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measured	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	



SECTION 8: Exposure controls/personal protection

Synergy 735

Hand protection	be w this i chec shou diffe seve estin	mical-resistant, impervious gloves complying with an approved standard should yorn at all times when handling chemical products if a risk assessment indicates is necessary. Considering the parameters specified by the glove manufacturer, ek during use that the gloves are still retaining their protective properties. It had be noted that the time to breakthrough for any glove material may be rent for different glove manufacturers. In the case of mixtures, consisting of eral substances, the protection time of the gloves cannot be accurately nated. Wear suitable gloves tested to EN374. Nitrile gloves. thickness 0.3 mm imum).
Body protection		onal protective equipment for the body should be selected based on the task gerformed and the risks involved before handling this product.
Other skin protection	seleo	opriate footwear and any additional skin protection measures should be cted based on the task being performed and the risks involved before handling product.
Respiratory protection	work	spirator is not needed under normal and intended conditions of product use. If ers are exposed to concentrations above the exposure limit, they must use opriate, certified respirators.
Environmental exposure controls	ensu In sc	ssions from ventilation or work process equipment should be checked to are they comply with the requirements of environmental protection legislation. The cases, fume scrubbers, filters or engineering modifications to the process pment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

3.1 information on pasic physica	ii and chemical properties
<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Yellow.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Pour point	: <0°C
Boiling point or initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	: Open cup: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
рН	: 7.5 to 8.5 [Conc. (% w/w): 5%]
Viscosity	 Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 47 mm²/s
Solubility	:
Not available.	
Solubility in water	: Not available.
Partition coefficient n-octanol/ water (log Pow)	: Not applicable.
Dispersibility properties	:

SECTION 9: Physical and chemical properties

Media	Result
cold water	Dispersible
hot water	Dispersible
Vapour pressure	: Not available.
Relative density	: Not available.
Density	: 1.059 g/cm³ [20°C]
Relative vapour density	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
9.2 Other information	
9.2.1 Information with reg	ard to physical hazard classes
Explosive properties	: Not available.
Oxidising properties	: Not available.
9.2.2 Other safety charact	eristics
Miscible with water	: Yes.
SECTION 10: Stabil	ity and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Shelf life: 24 months.

- **10.3 Possibility of** : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions
- **10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials : No specific data.
- **10.6 Hazardous**: Under normal conditions of storage and use, hazardous decomposition products
should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
neodecanoic acid	LD50 Dermal	Rat	3640 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2,2'-(cyclohexylimino) bisethanol	LD50 Oral	Rat	>2000 mg/kg	-
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	LC50 Inhalation Vapour	Rat	5.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1951 mg/kg	-

Acute toxicity estimates





SECTION 11: Toxicological information

		1			
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Synergy 735	>2000	N/A	N/A	N/A	N/A
neodecanoic acid	500	3640	N/A	N/A	N/A
2,2'-(cyclohexylimino)bisethanol	500	N/A	N/A	N/A	N/A
3,5,5-trimethylhexanoic acid	500 1951	N/A N/A	N/A N/A	N/A 11	N/A N/A
1,2-Ethanediamine, N1,N1,N2,N2-tetramethyl-, polymer with 1,1'-oxybis[2-chloroethane]	1951	N/A	IN/A	11	IN/A
Irritation/Corrosion					
Conclusion/Summary : Not available.					
Respiratory or skin sensitization					
Conclusion/Summary : Not available.					
<u>Mutagenicity</u>					
Conclusion/Summary : Not available.					
Carcinogenicity					
Conclusion/Summary : Not available.					
Reproductive toxicity					
Conclusion/Summary : Not available.					
<u>Teratogenicity</u>					
Conclusion/Summary : Not available.					
Specific target organ toxicity (single exposure	<u>e)</u>				

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-(cyclohexylimino)bisethanol	Category 2	-	gastrointestinal tract

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

SECTION 11: Toxicological information

Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
neodecanoic acid	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
2,2'-(cyclohexylimino) bisethanol	EC50 >100 mg/l	Fish	96 hours
1,2-Ethanediamine, N1,N1, N2,N2-tetramethyl-, polymer with 1,1'-oxybis [2-chloroethane]	Acute EC50 0.37 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l Fresh water Acute NOEC 0.037 mg/l Fresh water	Fish Fish	96 hours 96 hours

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
neodecanoic acid	2.1	<225	Low
3,5,5-trimethylhexanoic acid	3.2	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Blaser.



SECTION 12: Ecological information

Mobility

Synergy 735

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 01 10* 12 01 09*	synthetic machining oils machining emulsions and solutions free of halogens
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-		-	-
Date of issue/Date of re	vision : 4. Ma	r. 2025 Date of previous is	sue : 16. Jul. 2024	Version : 7 11/1



Synergy 735					
SECTION 14:	SECTION 14: Transport information				
14.5 Environmental hazards	No.	Yes.	No.	No.	
Additional information	tion		· · · · ·		
ADN		The product is only regulat vessels.	ed as a dangerous goo	d when transported in tank	
14.6 Special precautions for user : Transport within user's premises: always transport in closed containers to upright and secure. Ensure that persons transporting the product know what the event of an accident or spillage.					
14.7 Maritime trans bulk according to I instruments	· · · · · · · · · · · · · · · · · · ·				
SECTION 15.	Poqulator	vinformation			

CTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
Synergy 735	≥90	3	
Labelling : Not appli	cable.		
Other EU regulations			
Industrial emissions : Not listed (integrated pollution prevention and control) - Air	1		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water	1		
Explosive precursors : Not appli	cable.		
Ozone depleting substances (1005/200	<u>)9/EU)</u>		
Not listed.			
Prior Informed Consent (PIC) (649/2012	<u>2/EU)</u>		
Not listed.			
Persistent Organic Pollutants Not listed.			
Seveso Directive			
This product is not controlled under the S	eveso Direct	tive.	
National regulations			
Storage class (TRGS 510) : 12			
VOC content : Exempt.			

SECTION 15: Regu	-		
Hazardous liquids for water	: Class A		
International regulations			
	ntion List Schedules I, II & III Chemicals		
List name	Ingredient name		Status
Schedule III	Triethanolamine		Listed
Montreal Protocol			
Not listed.			
Stockholm Convention on	Persistent Organic Pollutants		
Not listed.			
	Prior Informed Consent (PIC)		
Not listed.			
UNECE Aarhus Protocol o	<u>n POPs and Heavy Metals</u>		
Not listed.			
5.2 Chemical safety	: This product contains substances for	which Chemical Safety Ass	essments are still
ssessment	required.		
SECTION 16: Other	information		
Indicates information that	t has changed from previously issued version	on.	
Abbreviations and	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Pa	ackaging Regulation [Regul	ation (EC) No
acronyms	1272/2008]		
	DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level		
	EUH statement = CLP-specific Hazar	d statement	
	N/A = Not available		
	PBT = Persistent, Bioaccumulative ar PNEC = Predicted No Effect Concent		
	RRN = REACH Registration Number	Tallon	
	SGG = Segregation Group		
	vPvB = Very Persistent and Very Bioa		
	he classification according to Regulation		
	Classification	Justificat	ion
Skin Irrit. 2, H315		Calculation method	
Eye Irrit. 2, H319 Aquatic Chronic 3, H412		Expert judgment Calculation method	
Full text of abbreviated H s	tatements		
	swallowed.		

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of printing	: 4. Mar 2025
Date of issue/ Date of	: 4. Mar. 2025
revision	
Date of previous issue	e : 16. Jul. 2024
Version	: 7
Responsible name	: Product Stewardship Blaser Swisslube AG

Blaser.

Notice to reader

To the best of our knowledge, the information contained herein is accurate.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.